



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-stop.1'

\$ man npm-stop.1

NPM-STOP(1)

NPM-STOP(1)

NAME

npm-stop - Stop a package

Synopsis

npm stop [-- <args>]

Description

This runs a predefined command specified in the "stop" property of a package's "scripts" object.

Unlike with npm help start, there is no default script that will run if the "stop" property is not defined.

Example

```
{
  "scripts": {
    "stop": "node bar.js"
  }
}
```

```
}
```

```
npm stop
```

```
> npm@x.x.x stop
```

```
> node bar.js
```

```
(bar.js output would be here)
```

Configuration

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->
```

ignore-scripts

? Default: false

? Type: Boolean

If true, npm does not run scripts specified in package.json files.

Note that commands explicitly intended to run a particular script, such as `npm start`, `npm stop`, `npm restart`, `npm test`, and `npm run-script` will still run their intended script if `ignore-scripts` is set, but they will not run any pre- or post-scripts. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

script-shell

? Default: '/bin/sh' on POSIX systems, 'cmd.exe' on Windows

? Type: null or String

The `shell` to use for scripts run with the `npm exec`, `npm run` and `npm init <pkg>` commands.

<!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

See Also

? `npm help run-script`

? `npm help scripts`

? `npm help test`

? `npm help start`

? `npm help restart`

undefined NaN

NPM-STOP(1)