



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-test.1'

\$ man npm-test.1

NPM-TEST(1)

NPM-TEST(1)

NAME

npm-test - Test a package

Synopsis

npm test [-- <args>]

aliases: t, tst

Description

This runs a predefined command specified in the "test" property of a package's "scripts" object.

Example

```
{
  "scripts": {
    "test": "node test.js"
  }
}
```

npm test

> npm@x.x.x test

> node test.js

(test.js output would be here)

Configuration

<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

ignore-scripts

? Default: false

? Type: Boolean

If true, npm does not run scripts specified in package.json files.

Note that commands explicitly intended to run a particular script, such as npm start, npm stop, npm restart, npm test, and npm run-script will still run their intended script if ignore-scripts is set, but they will not run any pre- or post-scripts. <!-- automatically generated, do not edit manually --> <!-- see lib/utls/config/definitions.js -->

script-shell

? Default: '/bin/sh' on POSIX systems, 'cmd.exe' on Windows

? Type: null or String

The shell to use for scripts run with the npm exec, npm run and npm init <pkg> commands.

<!-- automatically generated, do not edit manually --> <!-- see lib/utls/config/definitions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

See Also

? npm help run-script

? npm help scripts

? npm help start

? npm help restart

? npm help stop

undefined NaN

NPM-TEST(1)