



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'overlayroot-chroot.8'***

***\$ man overlayroot-chroot.8***

overlayroot-chroot(8)          initramfs-tools-overlayroot          overlayroot-chroot(8)

**NAME**

overlayroot-chroot - chroot into the lower filesystem in a writable mode

**SYNOPSIS**

overlayroot-chroot [COMMAND [ARG]...]

**DESCRIPTION**

overlayroot-chroot is a program that sets up bind mounts for /proc, /run, and /sys, re-mounts the lower directory in an overlaysfs with write capabilities and will chroot(8) into it. Upon exit, the bind mounts are unmounted.

Any [COMMAND [ARG]...] are passed directly through to chroot(8).

**SEE ALSO**

chroot(8)

**AUTHOR**

This manpage and the utility were written by Dustin Kirkland <kirkland@ubuntu.com> for Ubuntu systems (but may be used by others). Permission is granted to copy, distribute and/or modify this document and the utility under the terms of the GNU General Public License, Version 3 published by the Free Software Foundation.

The complete text of the GNU General Public License can be found in /usr/share/common-licenses/GPL on Debian/Ubuntu systems, or on the web at <http://www.gnu.org/licenses/gpl.txt>.

overlayroot-chroot          20 July 2012          overlayroot-chroot(8)