



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'pam_ftp.8'

\$ man pam_ftp.8

PAM_FTP(8) Linux-PAM Manual PAM_FTP(8)

NAME

pam_ftp - PAM module for anonymous access module

SYNOPSIS

pam_ftp.so [debug] [ignore] [users=XXX,YYY,...]

DESCRIPTION

pam_ftp is a PAM module which provides a pluggable anonymous ftp mode of access.

This module intercepts the user's name and password. If the name is ftp or anonymous, the user's password is broken up at the @ delimiter into a PAM_RUSER and a PAM_RHOST part; these pam-items being set accordingly. The username (PAM_USER) is set to ftp. In this case the module succeeds. Alternatively, the module sets the PAM_AUTHTOK item with the entered password and fails.

This module is not safe and easily spoofable.

OPTIONS

debug

Print debug information.

ignore

Pay no attention to the email address of the user (if supplied).

ftp=XXX,YYY,...

Instead of ftp or anonymous, provide anonymous login to the comma separated list of users: XXX,YYY,.... Should the applicant enter one of these usernames the returned username is set to the first in the list: XXX.

MODULE TYPES PROVIDED

Only the auth module type is provided.

RETURN VALUES

PAM_SUCCESS

The authentication was successful.

PAM_USER_UNKNOWN

User not known.

EXAMPLES

Add the following line to /etc/pam.d/ftpd to handle ftp style anonymous login:

```
#
# ftpd; add ftp-specifics. These lines enable anonymous ftp over
# standard UN*X access (the listfile entry blocks access to
# users listed in /etc/ftpusers)
#
auth sufficient pam_ftp.so
auth required pam_unix.so use_first_pass
auth required pam_listfile.so \
    onerr=succeed item=user sense=deny file=/etc/ftpusers
```

SEE ALSO

pam.conf(5), pam.d(5), pam(7)

AUTHOR

pam_ftp was written by Andrew G. Morgan <morgan@kernel.org>.