



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'pasuspender.1'***

***\$ man pasuspender.1***

pasuspender(1)                      General Commands Manual                      pasuspender(1)

NAME

pasuspender - Temporarily suspend PulseAudio

SYNOPSIS

pasuspender [options] -- PROGRAM [ARGUMENTS ...]

pasuspender --help

pasuspender --version

DESCRIPTION

pasuspender is a tool that can be used to tell a local PulseAudio sound server to temporarily suspend access to the audio devices, to allow other applications access them directly. pasuspender will suspend access to the audio devices, fork a child process, and when the child process terminates, resume access again.

Make sure to include -- in your pasuspender command line before passing the subprocess command line (as shown above). Otherwise pasuspender itself might end up interpreting the command line switches and options you intended to pass to the subprocess.

OPTIONS

-h | --help

Show help.

--version

Show version information.

-s | --server=SERVER

Specify the sound server to connect to.

AUTHORS

The PulseAudio Developers <pulseaudio-discuss (at) lists (dot) freedesktop (dot) org>;

PulseAudio is available from <http://pulseaudio.org/>

SEE ALSO

[pulseaudio\(1\)](#), [padsp\(1\)](#), [pacmd\(1\)](#), [pactl\(1\)](#)

[Manuals](#)

[User](#)

[pasuspender\(1\)](#)