

- If a FILENAME or DIRECTORY is passed as an argument, then it is first archived using tar(1) to preserve the file and directory attributes

pbget takes a URL as its first, mandatory argument. Optionally, it takes a DIRECTORY as a second parameter. If the incoming data is in fact a file or file structure in a tar(1) archive, then that data will be extracted in the specified DIRECTORY. If no DIRECTORY is specified, then a temporary directory is created using mktemp(1).

In any case the uploaded/downloaded data is optionally tar(1) archived, always lzma(1) compressed, optionally gpg(1) encrypted, and always base64(1) encoded. <http://paste?bin.com> is used by default.

EXAMPLES

```
$ pbput /sbin/init
http://pastebin.com/BstNzask
$ pbget http://pastebin.com/BstNzask
sbin/init
INFO: Output is in [/tmp/pbget.bG67DwY6ZI]
$ cat /etc/lsb-release | pbput
http://pastebin.com/p43gJv6Z
$ pbget http://pastebin.com/p43gJv6Z
DISTRIB_ID=Ubuntu
DISTRIB_RELEASE=11.04
DISTRIB_CODENAME=natty
DISTRIB_DESCRIPTION="Ubuntu 11.04"
$ pbputs /etc/shadow
Enter passphrase:
http://pastebin.com/t2ZaCYr3
$ pbget http://pastebin.com/t2ZaCYr3
Enter passphrase:
root:09cc6d2d9d63371a425076e217f77698:15096:0:99999:7:::
daemon:*:15089:0:99999:7:::
bin:*:15089:0:99999:7:::
sys:*:15089:0:99999:7:::
....
```

pastebinit(1), lzma(1), base64(1), tar(1), gpg(1), mktemp(1)

AUTHOR

This manpage and the utility was written by Dustin Kirkland <kirkland@ubuntu.com> for Ubuntu systems (but may be used by others). Permission is granted to copy, distribute and/or modify this document under the terms of the GNU General Public License, Version 2 or later published by the Free Software Foundation.

On Debian systems, the complete text of the GNU General Public License can be found in /usr/share/common-licenses/GPL, or on the web at <http://www.gnu.org/licenses/gpl.txt>.

bikeshed

6 Oct 2010

pbput(1)