



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-manifest-exists.1'***

***\$ man podman-manifest-exists.1***

```
podman-manifest-exists(1)()                podman-manifest-exists(1)()
```

**NAME**

podman-manifest-exists - Check if the given manifest list exists in local storage

**SYNOPSIS**

```
podman manifest exists manifest
```

**DESCRIPTION**

podman manifest exists checks if a manifest list exists on local storage. Podman will re? turn an exit code of 0 when the manifest is found. A 1 will be returned otherwise. An exit code of 125 indicates there was another issue.

**OPTIONS**

```
--help, -h
```

Print usage statement.

**EXAMPLE**

Check if a manifest list called list1 exists (the manifest list does actually exist).

```
$ podman manifest exists list1
```

```
$ echo $?
```

```
0
```

```
$
```

Check if an manifest called mylist exists (the manifest list does not actually exist).

```
$ podman manifest exists mylist
```

```
$ echo $?
```

```
1
```

```
$
```

## SEE ALSO

podman(1), podman-manifest-create(1), podman-manifest-remove(1)

## HISTORY

January 2021, Originally compiled by Paul Holzinger <paul.holzinger@web.de>

podman-manifest-exists(1)()