



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-pod-restart.1'

\$ man podman-pod-restart.1

podman-pod-restart(1)() podman-pod-restart(1)()

NAME

podman-pod-restart - Restart one or more pods

SYNOPSIS

podman pod restart [options] pod ...

DESCRIPTION

Restart containers in one or more pods. Containers will be stopped if running and then restarted. Stopped containers will only be started. You may use pod IDs or names as in? put. The pod ID will be printed upon successful restart. When restarting multiple pods, an error from restarting one pod will not effect restarting other pods.

OPTIONS

--all, -a

Restarts all pods

--latest, -l

Instead of providing the pod name or ID, restart the last created pod. (This option is not available with the remote Podman client)

EXAMPLE

```
podman pod restart mywebserverpod
```

```
cc8f0bea67b1a1a11aec1ecd38102a1be4b145577f21fc843c7c83b77fc28907
```

```
podman pod restart 490eb 3557fb
```

```
490eb241aaf704d4dd2629904410fe4aa31965d9310a735f8755267f4ded1de5
```

```
3557fbea6ad61569de0506fe037479bd9896603c31d3069a6677f23833916fab
```

```
podman pod restart --latest
```

3557f6ad61569de0506fe037479bd9896603c31d3069a6677f23833916fab

podman pod restart --all

19456b4cd557eaf9629825113a552681a6013f8c8cad258e36ab825ef536e818

3557f6ad61569de0506fe037479bd9896603c31d3069a6677f23833916fab

490eb241aaf704d4dd2629904410fe4aa31965d9310a735f8755267f4ded1de5

70c358daecf71ef9be8f62404f926080ca0133277ef7ce4f6aa2d5af6bb2d3e9

cc8f0bea67b1a1a11aec1ecd38102a1be4b145577f21fc843c7c83b77fc28907

SEE ALSO

podman-pod(1), podman-pod-start(1), podman-restart(1)

HISTORY

July 2018, Originally compiled by Peter Hunt pehunt@redhat.com ?mailto:pehunt@redhat.com?

podman-pod-restart(1)()