



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'podman-pod-start.1'***

***\$ man podman-pod-start.1***

podman-pod-start(1()) podman-pod-start(1())

NAME

podman-pod-start - Start one or more pods

SYNOPSIS

podman pod start [options] pod ...

DESCRIPTION

Start containers in one or more pods. You may use pod IDs or names as input. The pod must have a container attached to be started.

OPTIONS

--all, -a

Starts all pods

--latest, -l

Instead of providing the pod name or ID, start the last created pod. (This option is not available with the remote Podman client)

--pod-id-file

Read pod ID from the specified file and start the pod. Can be specified multiple times.

EXAMPLE

podman pod start mywebserverpod

podman pod start 860a4b23 5421ab4

podman pod start --latest

podman pod start --all

podman pod start --pod-id-file /path/to/id/file

SEE ALSO

podman-pod(1), podman-pod-stop(1), podman-start(1)

## HISTORY

July 2018, Adapted from podman start man page by Peter Hunt [pehunt@redhat.com](mailto:pehunt@redhat.com) ?mailto:pe? hunt@redhat.com?

podman-pod-start(1)()