Rocky Enterprise Linux 9.2 Manual Pages on command 'ppdhtml.1'

$ man ppdhtml.1

ppdhtml(1)   OpenPrinting   ppdhtml(1)

NAME

   ppdhtml - cups html summary generator (deprecated)

SYNOPSIS

   ppdhtml [-D name[=value]] [-I include-directory] source-file

DESCRIPTION

   ppdhtml reads a driver information file and produces a HTML summary page that lists all of

   the drivers in a file and the supported options. This program is deprecated and will be

   removed in a future release of CUPS.

OPTIONS

   ppdhtml supports the following options:

   -D name[=value]

      Sets the named variable for use in the source file. It is equivalent to using the

      #define directive in the source file.

   -I include-directory

      Specifies an alternate include directory. Multiple -I options can be supplied to add

      additional directories.

NOTES

PPD files are deprecated and will no longer be supported in a future feature release of CUPS. Printers that do not support IPP can be supported using applications such as ippeveprinter(1).

SEE ALSO

ppdc(1), ppdcfile(5), ppdi(1), ppdmerge(1), ppdpo(1), CUPS Online Help (http://local?host:631/help)

COPYRIGHT

Copyright ? 2021-2022 by OpenPrinting.

2021-02-28   CUPS   ppdhtml(1)