



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'readlink.1'

\$ man readlink.1

READLINK(1) User Commands READLINK(1)

NAME

readlink - print resolved symbolic links or canonical file names

SYNOPSIS

readlink [OPTION]... FILE...

DESCRIPTION

Note realpath(1) is the preferred command to use for canonicalization functionality.

Print value of a symbolic link or canonical file name

-f, --canonicalize

canonicalize by following every symlink in every component of the given name recursively; all but the last component must exist

-e, --canonicalize-existing

canonicalize by following every symlink in every component of the given name recursively, all components must exist

-m, --canonicalize-missing

canonicalize by following every symlink in every component of the given name recursively, without requirements on components existence

-n, --no-newline

do not output the trailing delimiter

-q, --quiet

-s, --silent

suppress most error messages (on by default)

-v, --verbose

report error messages

-z, --zero

end each output line with NUL, not newline

--help display this help and exit

--version

output version information and exit

AUTHOR

Written by Dmitry V. Levin.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2020 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

readlink(2), realpath(1), realpath(3)

Full documentation <<https://www.gnu.org/software/coreutils/readlink>>

or available locally via: info '(coreutils) readlink invocation'

GNU coreutils 8.32

February 2024

READLINK(1)