



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'remquof.3'***

**\$ man remquof.3**

REMQUO(3)                      Linux Programmer's Manual                      REMQUO(3)

**NAME**

remquo, remquof, remquol - remainder and part of quotient

**SYNOPSIS**

```
#include <math.h>

double remquo(double x, double y, int *quo);

float remquof(float x, float y, int *quo);

long double remquol(long double x, long double y, int *quo);

Link with -lm.
```

Feature Test Macro Requirements for glibc (see feature\_test\_macros(7)):

```
remquo(), remquof(), remquol():

    _ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

**DESCRIPTION**

These functions compute the remainder and part of the quotient upon division of x by y. A few bits of the quotient are stored via the quo pointer. The remainder is returned as the function result.

The value of the remainder is the same as that computed by the remainder(3) function.

The value stored via the quo pointer has the sign of x / y and agrees with the quotient in at least the low order 3 bits.

For example, remquo(29.0, 3.0) returns -1.0 and might store 2. Note that the actual quotient might not fit in an integer.

**RETURN VALUE**

On success, these functions return the same value as the analogous functions described in

remainder(3).

If x or y is a NaN, a NaN is returned.

If x is an infinity, and y is not a NaN, a domain error occurs, and a NaN is returned.

If y is zero, and x is not a NaN, a domain error occurs, and a NaN is returned.

## ERRORS

See math\_error(7) for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Domain error: x is an infinity or y is 0, and the other argument is not a NaN

An invalid floating-point exception (FE\_INVALID) is raised.

These functions do not set errno.

## VERSIONS

These functions first appeared in glibc in version 2.1.

## ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?remquo(), remquof(), remquol() ? Thread safety ? MT-Safe ?

??

## CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

## SEE ALSO

fmod(3), logb(3), remainder(3)

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.