Rocky Enterprise Linux 9.2 Manual Pages on command 'ri.1'

$ man ri.1

RI(1)   Ruby Programmer's Reference Guide   RI(1)

NAME

   ri ? Ruby API reference front end

SYNOPSIS

   ri [-ahilTv] [-d DIRNAME] [-f FORMAT] [-w WIDTH] [--[no-]pager] [--server[=PORT]]

     [--[no-]list-doc-dirs] [--no-standard-docs] [--[no-]{system|site|gems|home}]

     [--[no-]profile] [--dump=CACHE] [name ...]

DESCRIPTION

   ri is a command-line front end for the Ruby API reference. You can search and read the API

   reference for classes and methods with ri.

   ri is a part of Ruby.

   name can be:

       Class | Module | Module::Class

       Class::method | Class#method | Class.method | method

       gem_name: | gem_name:README | gem_name:History

   All class names may be abbreviated to their minimum unambiguous form. If a name is ambigu?

   ous, all valid options will be listed.

   A ?.? matches either class or instance methods, while #method matches only instance and

   ::method matches only class methods.

   README and other files may be displayed by prefixing them with the gem name they're con?

   tained in. If the gem name is followed by a ?:? all files in the gem will be shown. The

   file name extension may be omitted where it is unambiguous.

   For example:

ri Fil

    ri File

    ri File.new

    ri zip

    ri rdoc:README

Note that shell quoting or escaping may be required for method names containing punctuation:

    ri 'Array.[]'

    ri compact\!

To see the default directories ri will search, run:

    ri --list-doc-dirs

Specifying the --system, --site, --home, --gems, or --doc-dir options will limit ri to

searching only the specified directories.

ri options may be set in the RI environment variable.

The ri pager can be set with the RI_PAGER environment variable or the PAGER environment

variable.

OPTIONS

  -i

  --[no-]interactive

            In interactive mode you can repeatedly look up methods with autocomplete.

  -a

  --[no-]all   Show all documentation for a class or module.

  -l

  --[no-]list   List classes ri knows about.

  --[no-]pager   Send output to a pager, rather than directly to stdout.

  -T   Synonym for --no-pager.

  -w WIDTH

  --width=WIDTH   Set the width of the output.

  --server[=PORT]

            Run RDoc server on the given port. The default port is 8214.

  -f FORMAT

  --format=FORMAT

            Use the selected formatter. The default formatter is bs for paged output and

            ansi otherwise. Valid formatters are: ansi, bs, markdown, rdoc.

-h

--help   Show help and exit.

-v

--version   Output version information and exit.

Data source options:

--[no-]list-doc-dirs

        List the directories from which ri will source documentation on stdout and

        exit.

-d DIRNAME

--doc-dir=DIRNAME

        List of directories from which to source documentation in addition to the

        standard directories. May be repeated.

--no-standard-docs

        Do not include documentation from the Ruby standard library, site_lib, in?

        stalled gems, or ~/.rdoc. Use with --doc-dir.

--[no-]system Include documentation from Ruby's standard library. Defaults to true.

--[no-]site   Include documentation from libraries installed in site_lib. Defaults to

        true.

--[no-]gems   Include documentation from RubyGems. Defaults to true.

--[no-]home   Include documentation stored in ~/.rdoc. Defaults to true.

Debug options:

--[no-]profile

        Run with the Ruby profiler.

--dump=CACHE   Dump data from an ri cache or data file.

ENVIRONMENT

    RI   Options to prepend to those specified on the command-line.

    RI_PAGER

    PAGER   Pager program to use for displaying.

    HOME

    USERPROFILE

    HOMEPATH   Path to the user's home directory.

FILES

    ~/.rdoc   Path for ri data in the user's home directory.

SEE ALSO

ruby(1), rdoc(1), gem(1)

REPORTING BUGS

? Security vulnerabilities should be reported via an email to security@ruby-lang.org. Re?

ported problems will be published after being fixed.

? Other bugs and feature requests can be reported via the Ruby Issue Tracking System

(https://bugs.ruby-lang.org/). Do not report security vulnerabilities via this system

because it publishes the vulnerabilities immediately.

AUTHORS

Written by Dave Thomas <dave@pragmaticprogrammer.com>.

UNIX   April 20, 2017   UNIX