Rocky Enterprise Linux 9.2 Manual Pages on command 'rmmod.8'

$ man rmmod.8

RMMOD(8)   rmmod   RMMOD(8)

NAME

   rmmod - Simple program to remove a module from the Linux Kernel

SYNOPSIS

   rmmod [-f] [-s] [-v] [modulename]

DESCRIPTION

   rmmod is a trivial program to remove a module (when module unloading support is provided)

   from the kernel. Most users will want to use modprobe(8) with the -r option instead.

OPTIONS

   -v, --verbose

      Print messages about what the program is doing. Usually rmmod prints messages only if

      something goes wrong.

   -f, --force

      This option can be extremely dangerous: it has no effect unless

      CONFIG_MODULE_FORCE_UNLOAD was set when the kernel was compiled. With this option, you

      can remove modules which are being used, or which are not designed to be removed, or

      have been marked as unsafe (see lsmod(8)).

   -s, --syslog

      Send errors to syslog instead of standard error.

   -V --version

      Show version of program and exit.

COPYRIGHT

   This manual page originally Copyright 2002, Rusty Russell, IBM Corporation. Maintained by

Jon Masters and others.

SEE ALSO

modprobe(8), insmod(8), lsmod(8), modinfo(8) depmod(8)

AUTHORS

Jon Masters <jcm@jonmasters.org>

Developer

Lucas De Marchi <lucas.de.marchi@gmail.com>

Developer