



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'rt\_tgsigqueueinfo.2'***

***\$ man rt\_tgsigqueueinfo.2***

RT\_SIGQUEUEINFO(2)                      Linux Programmer's Manual                      RT\_SIGQUEUEINFO(2)

NAME

rt\_sigqueueinfo, rt\_tgsigqueueinfo - queue a signal and data

SYNOPSIS

```
int rt_sigqueueinfo(pid_t tgid, int sig, siginfo_t *info);
int rt_tgsigqueueinfo(pid_t tgid, pid_t tid, int sig,
                     siginfo_t *info);
```

Note: There are no glibc wrappers for these system calls; see NOTES.

DESCRIPTION

The `rt_sigqueueinfo()` and `rt_tgsigqueueinfo()` system calls are the low-level interfaces used to send a signal plus data to a process or thread. The receiver of the signal can obtain the accompanying data by establishing a signal handler with the `sigaction(2)` `SA_SIGINFO` flag.

These system calls are not intended for direct application use; they are provided to allow the implementation of `sigqueue(3)` and `pthread_sigqueue(3)`.

The `rt_sigqueueinfo()` system call sends the signal `sig` to the thread group with the ID `tgid`. (The term "thread group" is synonymous with "process", and `tid` corresponds to the traditional UNIX process ID.) The signal will be delivered to an arbitrary member of the thread group (i.e., one of the threads that is not currently blocking the signal).

The `info` argument specifies the data to accompany the signal. This argument is a pointer to a structure of type `siginfo_t`, described in `sigaction(2)` (and defined by including `<sigaction.h>`). The caller should set the following fields in this structure:

`si_code`

This should be one of the SI\_\* codes in the Linux kernel source file include/asm-generic/signinfo.h. If the signal is being sent to any process other than the caller itself, the following restrictions apply:

- \* The code can't be a value greater than or equal to zero. In particular, it can't be SI\_USER, which is used by the kernel to indicate a signal sent by kill(2), and nor can it be SI\_KERNEL, which is used to indicate a signal generated by the kernel.
- \* The code can't (since Linux 2.6.39) be SI\_TKILL, which is used by the kernel to indicate a signal sent using tkill(2).

si\_pid This should be set to a process ID, typically the process ID of the sender.

si\_uid This should be set to a user ID, typically the real user ID of the sender.

si\_value

This field contains the user data to accompany the signal. For more information, see the description of the last (union signal) argument of sigqueue(3).

Internally, the kernel sets the si\_signo field to the value specified in sig, so that the receiver of the signal can also obtain the signal number via that field.

The rt\_tsigqueueinfo() system call is like rt\_sigqueueinfo(), but sends the signal and data to the single thread specified by the combination of tgid, a thread group ID, and tid, a thread in that thread group.

## RETURN VALUE

On success, these system calls return 0. On error, they return -1 and errno is set to indicate the error.

## ERRORS

EAGAIN The limit of signals which may be queued has been reached. (See signal(7) for further information.)

EINVAL sig, tgid, or tid was invalid.

EPERM The caller does not have permission to send the signal to the target. For the required permissions, see kill(2).

EPERM tgid specifies a process other than the caller and info->si\_code is invalid.

ESRCH rt\_sigqueueinfo(): No thread group matching tgid was found.

rt\_tsigqueueinfo(): No thread matching tgid and tid was found.

## VERSIONS

The rt\_sigqueueinfo() system call was added to Linux in version 2.2. The rt\_tsigqueueinfo()

info() system call was added to Linux in version 2.6.31.

## CONFORMING TO

These system calls are Linux-specific.

## NOTES

Since these system calls are not intended for application use, there are no glibc wrapper functions; use `syscall(2)` in the unlikely case that you want to call them directly.

As with `kill(2)`, the null signal (0) can be used to check if the specified process or thread exists.

## SEE ALSO

`kill(2)`, `pidfd_send_signal(2)`, `sigaction(2)`, `sigprocmask(2)`, `tgkill(2)`,  
`pthread_sigqueue(3)`, `sigqueue(3)`, `signal(7)`

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.