



## ***Linux Ubuntu 22.4.5 Manual Pages on command 'runc-create.8'***

### ***\$ man runc-create.8***

runc-create (8"") runc-create (8"")

#### NAME

runc-create - create a container

#### SYNOPSIS

runc create [option ...] container-id

#### DESCRIPTION

The create command creates an instance of a container from a bundle. The bundle is a directory with a specification file named config.json, and a root filesystem.

#### OPTIONS

--bundle|-b path : Path to the root of the bundle directory. Default is current directory.

--console-socket path : Path to an AF\_UNIX socket which will receive a file descriptor referencing the master end of the console's pseudoterminal. See docs/terminals

?<https://github.com/opencontainers/runc/blob/master/docs/terminals.md>?

--pid-file path : Specify the file to write the initial container process' PID to.

--no-pivot : Do not use pivot root to jail process inside rootfs. This should not be used except in exceptional circumstances, and may be unsafe from the security standpoint.

--no-new-keyring : Do not create a new session keyring for the container. This will cause the container to inherit the calling processes session key.

--preserve-fds N : Pass N additional file descriptors to the container (stdio +

\$LISTEN\_FDS + N in total). Default is 0.

#### SEE ALSO

runc-spec(8), runc-start(8), runc(8).

runc-create (8")