

Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'sane-hp5400.5'

\$ man sane-hp5400.5

sane-hp5400(5)

SANE Scanner Access Now Easy

sane-hp5400(5)

NAME

sane-hp5400 - SANE backend for Hewlett-Packard 54XX scanners

DESCRIPTION

The sane-hp5400 library implements a SANE (Scanner Access Now Easy) backend that provides access to the following Hewlett-Packard USB flatbed scanners:

ScanJet 5400C

ScanJet 5470C

ScanJet 5490C

More details can be found on the hp5400 backend homepage http://hp5400backend.source? forge.net/.

This is ALPHA software. Keep your hand at the scanner's plug and unplug it, if the head bumps at the end of the scan area. See also the BUGS section.

If you own a scanner other than the ones listed above that works with this backend, please let us know this by sending the scanner's exact model name and the USB vendor and device ids (e.g. from /proc/bus/usb/devices, sane-find-scanner(1) or syslog) to us. Even if the scanner's name is only slightly different from the models mentioned above, please let us

know.

CONFIGURATION

The contents of the hp5400.conf file is a list of usb lines containing vendor and product ids that correspond to USB scanners. The file can also contain the names of device files that correspond to an HP 54XX scanner. Empty lines and lines starting with a hash mark (#) are ignored. The scanners are autodetected by usb vendor_id product_id statements which are already included into hp5400.conf. "vendor_id" and "product_id" are hexadecimal numbers that identify the scanner. If autodetection does not work, add the device name of your scanner to the configuration file, e.g. /dev/usb/scanner0.

FILES

/etc/sane.d/hp5400.conf

The backend configuration file (see also description of SANE_CONFIG_DIR below).

/usr/lib/x86_64-linux-gnu/sane/libsane-hp5400.a

The static library implementing this backend.

/usr/lib/x86_64-linux-gnu/sane/libsane-hp5400.so

The shared library implementing this backend (present on systems that support dy? namic loading).

ENVIRONMENT

SANE_CONFIG_DIR

This environment variable specifies the list of directories that may contain the configuration file. On *NIX systems, the directories are separated by a colon (`:'), under OS/2, they are separated by a semi-colon (`;'). If this variable is not set, the configuration file is searched in two default directories: first, the current working directory (.) and then in /etc/sane.d. If the value of the envi? ronment variable ends with the directory separator character, then the default di? rectories are searched after the explicitly specified directories. For example, setting SANE_CONFIG_DIR to "/tmp/config:" would result in directories tmp/config, ., and /etc/sane.d being searched (in this order).

SANE_DEBUG_HP5400

If the library was compiled with debug support enabled, this environment variable

controls the debug level for this backend. Higher debug levels increase the ver?

bosity of the output.

Example: export SANE_DEBUG_HP5400=4

SEE ALSO

sane(7), sane-usb(5), sane-find-scanner(1),

http://hp5400backend.sourceforge.net/

AUTHOR

Martijn van Oosterhout <kleptog@svana.org>, Thomas Soumarmon <soumarmt@nerim.net>. Man?

page by Henning Meier-Geinitz <henning@meier-geinitz.de>.

BUGS

Scanning is only tested with Linux/ix86/gcc. Be careful when testing on other operating

systems and especially on big-endian platforms. The scanner may get wrong data.

13 Jul 2008

sane-hp5400(5)