



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'sane-s9036.5'

\$ man sane-s9036.5

sane-s9036(5) SANE Scanner Access Now Easy sane-s9036(5)

NAME

sane-s9036 - SANE backend for Siemens 9036 flatbed scanners

DESCRIPTION

The sane-s9036 library implements a SANE (Scanner Access Now Easy) backend that provides access to Siemens 9036 flatbed scanners.

DEVICE NAMES

This backend expects device names of the form:

special

Where special is the path-name for the special device that corresponds to a SCSI scanner.

The special device name must be a generic SCSI device or a symlink to such a device. The program sane-find-scanner(1) helps to find out the correct device. Under Linux, such a device name could be /dev/sga or /dev/sge, for example. See sane-scsi(5) for details.

FILES

/etc/sane.d/s9036.conf

The backend configuration file (see also description of SANE_CONFIG_DIR below).

/usr/lib/x86_64-linux-gnu/sane/libsane-s9036.a

The static library implementing this backend.

/usr/lib/x86_64-linux-gnu/sane/libsane-s9036.so

The shared library implementing this backend (present on systems that support dynamic loading).

ENVIRONMENT

SANE_CONFIG_DIR

This environment variable specifies the list of directories that may contain the configuration file. On *NIX systems, the directories are separated by a colon (:), under OS/2, they are separated by a semi-colon (;). If this variable is not set, the configuration file is searched in two default directories: first, the current working directory (".") and then in /etc/sane.d. If the value of the environment variable ends with the directory separator character, then the default directories are searched after the explicitly specified directories. For example, setting SANE_CONFIG_DIR to "/tmp/config:" would result in directories tmp/config, ., and /etc/sane.d being searched (in this order).

SANE_DEBUG_S9036

If the library was compiled with debug support enabled, this environment variable controls the debug level for this backend. Higher debug levels increase the verbosity of the output.

Example: export SANE_DEBUG_S9036=4

SEE ALSO

sane(7), sane-scsi(5)

AUTHOR

Ingo Schneider