Rocky Enterprise Linux 9.2 Manual Pages on command 'setvtrgb.1'

$ man setvtrgb.1

SETVTRGB(1)   General Commands Manual   SETVTRGB(1)

NAME

    setvtrgb - customize the console color map

SYNOPSIS

    setvtrgb vga

    setvtrgb FILE|-

DESCRIPTION

    setvtrgb sets the console color map in all virtual terminals according to custom values

    specified in a file or standard input. With the `vga' parameter, it can also be used to

    restore the settings built into the kernel.

    When invoked with a filename or `-', setvtrgb expects input as follows:

    color0_r,color1_r,...,color15_r

    color0_g,color1_g,...,color15_g

    color0_b,color1_b,...,color15_b

    where colorN_{r,g,b} is the red/green/blue portion of the respective color in decimal no?

    tation in the 0..255 range. To pre-seed a file in the correct format, you can use

    cat /sys/module/vt/parameters/default_{red,grn,blu}

    The meanings of the color values are defined as follows:

    +--------+-------+---------+

    | Normal | Bright | Color |

    +--------+-------+---------+

    | 0 | 8 | Black |

    | 1 | 9 | Red |

```
|    2 |    10 | Green   |

|    3 |    11 | Yellow  |

|    4 |    12 | Blue    |

|    5 |    13 | Magenta |

|    6 |    14 | Cyan    |

|    7 |    15 | White   |

+--------------------------+
```

AUTHOR

setvtrgb is Copyright ? 2011 Alexey Gladkov <gladkov.alexey@gmail.com>, with portions by
Dustin Kirkland <kirkland@canonical.com> and Seth Forshee <seth.forshee@canonical.com> at
Canonical Ltd.

This manual page was written by Michael Schutte <michi@debian.org> for the Debian
GNU/Linux system (but may be used by others).

<div align="center">

July 2011   SETVTRGB(1)

</div>