



patible with XCOPY as defined in SPC-3, some of the command naming has changed. This utility uses the older, SPC-3 XCOPY names.

The ddpt utility supports the same xcopy(LID1) functionality as this utility with the same options and flags. Additionally ddpt supports a subset of xcopy(LID4) functionality vari-  
ously called "xcopy version 2, lite" or ODX. ODX is a market name and stands for Off-  
loaded Data Xfer (i.e. transfer).

## OPTIONS

app={0|1}

if 1 start the destination of the copy at the end of OFILE. This assumes that OFILE is a regular file. The default is 0 in which case the destination of the copy starts at the beginning of OFILE (possibly offset by SEEK). This option cannot be used with the seek=SEEK option.

bpt=BPT

each IO transaction will be made using BPT blocks (or less if near the end of the copy). Default is 128 for logical block sizes less than 2048 bytes, otherwise the default is 32. So for bs=512 the reads and writes will each convey 64 KiB of data by default (less if near the end of the transfer or memory restrictions). When cd/dvd drives are accessed, the logical block size is typically 2048 bytes and bpt defaults to 32 which again implies 64 KiB transfers.

bs=BS where BS must be the logical block size of the physical device (if either the input or output files are accessed via SCSI commands). Note that this differs from dd(1) which permits BS to be an integral multiple. Defaults to the device logical block size.

cat={0|1}

sets the SCSI EXTENDED COPY command segment descriptor CAT bit to 0 or 1 (default: 0). The CAT bit (in conjunction with the PAD bit) controls the handling of residual data. See section HANDLING OF RESIDUAL DATA for details.

conv=CONV

all CONV arguments are ignored.

count=COUNT

copy COUNT blocks from IFILE to OFILE. Default is the minimum (IFILE if dc=0 or OFILE if dc=1) number of blocks that SCSI devices report from SCSI READ CAPACITY commands or that block devices (or their partitions) report. Normal files are not

probed for their size. If skip=SKIP or seek=SEEK are given and the count is derived (i.e. not explicitly given) then the derived count is scaled back so that the copy will not overrun the device. If the file name is a block device partition and COUNT is not given then the size of the partition rather than the size of the whole device is used. If COUNT is not given (or count=-1) and cannot be derived then an error message is issued and no copy takes place.

dc={0|1}

sets the SCSI EXTENDED COPY command segment descriptor DC bit to 0 or 1 (default: 0). The DC bit controls whether COUNT refers to the source (dc=0) or the target (dc=1) descriptor.

fco={0|1}

sets the SCSI EXTENDED COPY command segment descriptor FCO bit to 0 or 1 (default: 0). The Fast Copy Only (FCO) bit set will result in the copy being done but a technique faster than SCSI READ and WRITE commands. If the copy cannot be done in a faster manner then a sense key of "Copy aborted" with an additional sense of "Fast copy not possible" is returned.

ibs=BS if given must be the same as BS given to 'bs=' option.

id\_usage={hold|discard|disable}

sets the SCSI EXTENDED COPY command parameter list field called LIST ID USAGE to 0 if the argument is 'hold', to 2 if the argument is 'discard', or to '3' if the argument is 'disable'.

If the device has the ability to hold data (as indicated by "held data limit" being greater than zero) then id\_usage defaults to 'hold' otherwise it defaults to 'discard'.

if=IFILE

read from IFILE instead of stdin. If IFILE is '-' then stdin is read. Starts reading at the beginning of IFILE unless SKIP is given.

iflag=FLAGS

where FLAGS is a comma separated list of one or more flags outlined below. These flags are associated with IFILE and are ignored when IFILE is stdin.

list\_id=ID

sets the SCSI EXTENDED COPY command parameter list field called LIST IDENTIFIER to ID. ID should be a value between 0 and 255 (inclusive). ID usually defaults to 1

unless `id_usage=disable` in which case it defaults to 0.

`obs=BS` if given must be the same as `BS` given to `'bs='` option.

`of=OFILE`

write to `OFILE` instead of `stdout`. If `OFILE` is `'-'` then writes to `stdout`. If `OFILE` is `/dev/null` then no actual writes are performed. If `OFILE` is `'.'` (period) then it is treated the same way as `/dev/null` (this is a shorthand notation). If `OFILE` exists then it is `_not_` truncated; it is overwritten from the start of `OFILE` unless `'oflag=append'` or `SEEK` is given.

`oflag=FLAGS`

where `FLAGS` is a comma separated list of one or more flags outlined below. These flags are associated with `OFILE` and are ignored when `OFILE` is `/dev/null`, `'.'` (period), or `stdout`.

`prio=PRIO`

sets the SCSI EXTENDED COPY command parameter list field called `PRIORITY` to `PRIO`.  
The default value is 1.

`seek=SEEK`

start writing `SEEK` `bs`-sized blocks from the start of `OFILE`. Default is block 0 (i.e. start of file).

`skip=SKIP`

start reading `SKIP` `bs`-sized blocks from the start of `IFILE`. Default is block 0 (i.e. start of file).

`time={0|1}`

when 1, times transfer and does throughput calculation, outputting the results (to `stderr`) at completion. When 0 (default) doesn't perform timing.

`verbose=VERB`

as `VERB` increases so does the amount of debug output sent to `stderr`. Default value is zero which yields the minimum amount of debug output. A value of 1 reports extra information that is not repetitive. A value 2 reports `cmds` and responses for SCSI commands that are not repetitive (i.e. other than `READ` and `WRITE`). Error processing is not considered repetitive. Values of 3 and 4 yield output for all SCSI commands (and Unix `read()` and `write()` calls) so there can be a lot of output.

`-h, --help`

outputs usage message and exits.

--on\_dst

send the XCOPY command to the output file/device (i.e. OFILE). This is the default unless overridden by the --on\_src or iflag=xflag options. Also see the section below on ENVIRONMENT VARIABLES.

--on\_src

send the XCOPY command to the input file/device (i.e. IFILE).

-v, --verbose

equivalent to verbose=1. When used twice, equivalent to verbose=2, etc.

-V, --version

outputs version number information and exits.

## FLAGS

Here is a list of flags and their meanings:

append causes the O\_APPEND flag to be added to the open of OFILE. For regular files this will lead to data appended to the end of any existing data. Cannot be used together with the seek=SEEK option as they conflict. The default action of this utility is to overwrite any existing data from the beginning of the file or, if SEEK is given, starting at block SEEK. Note that attempting to 'append' to a device file (e.g. a disk) will usually be ignored or may cause an error to be reported.

excl causes the O\_EXCL flag to be added to the open of IFILE and/or OFILE.

flock after opening the associated file (i.e. IFILE and/or OFILE) an attempt is made to get an advisory exclusive lock with the flock() system call. The flock arguments are "FLOCK\_EX | FLOCK\_NB" which will cause the lock to be taken if available else a "temporarily unavailable" error is generated. An exit status of 90 is produced in the latter case and no copy is done.

null has no affect, just a placeholder.

pad sets the SCSI EXTENDED COPY command segment descriptor PAD bit. The PAD bit (in conjunction with the CAT bit) controls the handling of residual data.(See section HANDLING OF RESIDUAL DATA for details.

xcopy has no affect; for compatibility with ddpt.

## HANDLING OF RESIDUAL DATA

The pad and cat bits control the handling of residual data. As the data can be specified either in terms of source or target logical block size and both might have different block sizes residual data is likely to happen in these cases. If both logical block sizes are

identical these bits have no effect as residual data will not occur.

If none of these bits are set, the EXTENDED COPY command will be aborted with additional sense 'UNEXPECTED INEXACT SEGMENT'.

If only the cat bit is set the residual data will be retained and made available for subsequent segment descriptors. Residual data will be discarded for the last segment descriptor.

If the pad bit is set for the source descriptor only, any residual data for both source or destination will be discarded.

If the pad bit is set for the target descriptor only any residual source data will be handled as if the cat bit is set, but any residual destination data will be padded to make a whole block transfer.

If the pad bit is set for both source and target any residual source data will be discarded, and any residual destination data will be padded.

## ENVIRONMENT VARIABLES

If the command line invocation does not explicitly (and unambiguously) indicate whether the XCOPY SCSI command should be sent to IFILE (i.e. the source) or OFILE (i.e. the destination) then a check is made for the presence of the XCOPY\_TO\_SRC and XCOPY\_TO\_DST environment variables. If either one exists (but not both) then it indicates where the SCSI XCOPY command will be sent. By default the XCOPY command is sent to OFILE.

## RETIRED OPTIONS

Here are some retired options that are still present:

append=0 | 1

when set, equivalent to 'oflag=append'. When clear the action is to overwrite the existing file (if it exists); this is the default. See the 'append' flag.

## NOTES

Copying data behind an Operating System's back can cause problems. In the case of Linux, users should look at this link: [http://linux-mm.org/Drop\\_Caches](http://linux-mm.org/Drop_Caches)

This command sequence may be useful:

```
sync; echo 3 > /proc/sys/vm/drop_caches
```

Various numeric arguments (e.g. SKIP) may include multiplicative suffixes or be given in hexadecimal. See the "NUMERIC ARGUMENTS" section in the sg3\_utils(8) man page.

The COUNT, SKIP and SEEK arguments can take 64 bit values (i.e. very big numbers). Other values are limited to what can fit in a signed 32 bit number.

All informative, warning and error output is sent to stderr so that dd's output file can be stdout and remain unpolluted. If no options are given, then the usage message is output and nothing else happens.

If a device supports xcopy operations then it should set the 3PC field (3PC stands for Third Party Copy) in its standard INQUIRY response. This utility will attempt a xcopy operation irrespective of the value in the 3PC field but if it is zero (cleared) one would expect the xcopy operation to fail.

The status of the SCSI EXTENDED COPY command can be queried with `sg_copy_results(``sg3_utils)`

Currently only block-to-block transfers are implemented; IFILE and OFILE must refer to a SCSI block device.

No account is taken of partitions so, for example, `/dev/sbc2`, `/dev/sdc`, `/dev/sg2`, and `/dev/bsg/3:0:0:1` would all refer to the same thing: the whole logical unit (i.e. the whole disk) starting at LBA 0. So any partition indication (e.g. `/dev/sdc2`) is ignored. The user should set SKIP, SEEK and COUNT with information obtained from a command like `'fdisk -l -u /dev/sdc'` to account for partitions.

XCOPY (LID1) capability has been added to the `ddpt` utility which is in a package of the same name. The `ddpt` utility will run on other OSes (e.g. FreeBSD and Windows) while `sg_xcopy` only runs on Linux. Also `ddpt` permits the arguments to `ibs=` and `obs=` to be different.

## EXAMPLES

Copy 2M of data from the start of one device to another:

```
# sg_xcopy if=/dev/sdo of=/dev/sdp count=2048 list_id=2 dc=1
```

```
sg_xcopy: if=/dev/sdo skip=0 of=/dev/sdp seek=0 count=1024
```

```
Start of loop, count=1024, bpt=65535, lba_in=0, lba_out=0
```

```
sg_xcopy: 1024 blocks, 1 command
```

Check the status of the EXTENDED COPY command:

```
# sg_copy_results --status --list_id=2 /dev/sdp
```

Receive copy results (copy status):

```
Held data discarded: Yes
```

```
Copy manager status: Operation completed without errors
```

```
Segments processed: 1
```

```
Transfer count units: 0
```

Transfer count: 0

## SIGNALS

The signal handling has been borrowed from dd: SIGINT, SIGQUIT and SIGPIPE output the number of remaining blocks to be transferred and the records in + out counts; then they have their default action. SIGUSR1 causes the same information to be output yet the copy continues. All output caused by signals is sent to stderr.

## EXIT STATUS

The exit status of sg\_xcopy is 0 when it is successful. Otherwise see the sg3\_utils(8) man page.

An additional exit status of 90 is generated if the flock flag is given and some other process holds the advisory exclusive lock.

## AUTHORS

Written by Hannes Reinecke and Douglas Gilbert.

## REPORTING BUGS

Report bugs to <dgilbert at interlog dot com>.

## COPYRIGHT

Copyright ? 2000-2019 Hannes Reinecke and Douglas Gilbert

This software is distributed under the GPL version 2. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

## SEE ALSO

There is a web page discussing sg\_dd at [http://sg.danny.cz/sg/sg\\_dd.html](http://sg.danny.cz/sg/sg_dd.html)

A POSIX threads version of this utility called sgp\_dd is in the sg3\_utils package. Another version from that package is called sgm\_dd and it uses memory mapped IO to speed transfers from sg devices.

The lmbench package contains lmddd which is also interesting. For moving data to and from tapes see dt which is found at [http://www.scsifaq.org/RMiller\\_Tools/index.html](http://www.scsifaq.org/RMiller_Tools/index.html)

To change mode parameters that effect a SCSI device's caching and error recovery see sdparm(sdparm)

See also dd(1), sg\_copy\_results(sg3\_utils), ddrescue(GNU), ddpt, ddptctl(ddpt)