

Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'sigpause.3'

\$ man sigpause.3

SIGPAUSE(3)

Linux Programmer's Manual

SIGPAUSE(3)

NAME

sigpause - atomically release blocked signals and wait for interrupt

SYNOPSIS

#include <signal.h>

int sigpause(int sigmask); /* BSD (but see NOTES) */

int sigpause(int sig); /* System V / UNIX 95 */

DESCRIPTION

Don't use this function. Use sigsuspend(2) instead.

The function sigpause() is designed to wait for some signal. It changes the process's signal mask (set of blocked signals), and then waits for a signal to arrive. Upon arrival of a signal, the original signal mask is restored.

RETURN VALUE

If sigpause() returns, it was interrupted by a signal and the return value is -1 with er? rno set to EINTR.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

?Interface ? Attribute ? Value ?

?????????????????????????????????????

?sigpause() ? Thread safety ? MT-Safe ?

????????????????????????????????????

CONFORMING TO Page 1/2

The System V version of sigpause() is standardized in POSIX.1-2001. It is also specified in POSIX.1-2008, where it is marked obsolete.

NOTES

History

The classical BSD version of this function appeared in 4.2BSD. It sets the process's sig? nal mask to sigmask. UNIX 95 standardized the incompatible System V version of this func? tion, which removes only the specified signal sig from the process's signal mask. The un? fortunate situation with two incompatible functions with the same name was solved by the sigsuspend(2) function, that takes a sigset_t * argument (instead of an int).

Linux notes

On Linux, this routine is a system call only on the Sparc (sparc64) architecture.

Glibc uses the BSD version if the _BSD_SOURCE feature test macro is defined and none of _POSIX_SOURCE, _POSIX_C_SOURCE, _XOPEN_SOURCE, _GNU_SOURCE, or _SVID_SOURCE is defined. Otherwise, the System V version is used, and feature test macros must be defined as fol? lows to obtain the declaration:

- * Since glibc 2.26: _XOPEN_SOURCE >= 500
- * Glibc 2.25 and earlier: _XOPEN_SOURCE

Since glibc 2.19, only the System V version is exposed by <signal.h>; applications that formerly used the BSD signalse() should be amended to use sigsuspend(2).

SEE ALSO

kill(2), sigaction(2), sigprocmask(2), sigsuspend(2), sigblock(3), sigvec(3), fea?
ture_test_macros(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

Linux 2017-09-15 SIGPAUSE(3)