



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'snap-discard-ns.8'***

**\$ man snap-discard-ns.8**

SNAP-DISCARD-NS(5)                      snappy                      SNAP-DISCARD-NS(5)

#### NAME

snap-discard-ns - internal tool for discarding preserved namespaces of snappy applications

#### SYNOPSIS

snap-discard-ns [--from-snap-confine] SNAP\_INSTANCE\_NAME

#### DESCRIPTION

The snap-discard-ns is a program used internally by snapd to discard a preserved mount namespace of a particular snap.

#### OPTIONS

The --from-snap-confine option is used internally by snap-confine to tell snap-discard-ns that it is invoked from snap-confine and can disable locking.

#### ENVIRONMENT

snap-discard-ns responds to the following environment variables

##### SNAP\_CONFINE\_DEBUG:

When defined the program will print additional diagnostic information about the actions being performed. All the output goes to stderr.

## FILES

snap-discard-ns uses the following files:

`/run/snapd/ns/$SNAP_INSTNACE_NAME.mnt: /run/snapd/ns/$SNAP_INSTNACE_NAME.*.mnt:`

The preserved mount namespace that is unmounted and removed by snap-discard-ns. The second form is for the per-user mount namespace.

`/run/snapd/ns/snap.$SNAP_INSTNACE_NAME.fstab: /run/snapd/ns/snap.$SNAP_INSTNACE_NAME.*.user-fstab:`

The current mount profile of a preserved mount namespace that is removed by snap-discard-ns.

## BUGS

Please report all bugs with <https://bugs.launchpad.net/snapd/+filebug>

## AUTHOR

[zygmunt.krynicki@canonical.com](mailto:zygmunt.krynicki@canonical.com)

## COPYRIGHT

Canonical Ltd.

2.36

2018-10-17

SNAP-DISCARD-NS(5)