



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'strtof.3'

\$ man strtof.3

STRTOF(3) Linux Programmer's Manual STRTOF(3)

NAME

strtod, strtod, strtold - convert ASCII string to floating-point number

SYNOPSIS

```
#include <stdlib.h>

double strtod(const char *nptr, char **endptr);

float strtod(const char *nptr, char **endptr);

long double strtold(const char *nptr, char **endptr);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
strtod(), strtold():

    _ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

The strtod(), strtod(), and strtold() functions convert the initial portion of the string pointed to by nptr to double, float, and long double representation, respectively.

The expected form of the (initial portion of the) string is optional leading white space as recognized by isspace(3), an optional plus ('+') or minus sign ('-') and then either (i) a decimal number, or (ii) a hexadecimal number, or (iii) an infinity, or (iv) a NAN (not-a-number).

A decimal number consists of a nonempty sequence of decimal digits possibly containing a radix character (decimal point, locale-dependent, usually '.'), optionally followed by a decimal exponent. A decimal exponent consists of an 'E' or 'e', followed by an optional plus or minus sign, followed by a nonempty sequence of decimal digits, and indicates multiplication by a power of 10.

A hexadecimal number consists of a "0x" or "0X" followed by a nonempty sequence of hexadecimal digits possibly containing a radix character, optionally followed by a binary exponent. A binary exponent consists of a 'P' or 'p', followed by an optional plus or minus sign, followed by a nonempty sequence of decimal digits, and indicates multiplication by a power of 2. At least one of radix character and binary exponent must be present.

An infinity is either "INF" or "INFINITY", disregarding case.

A NAN is "NAN" (disregarding case) optionally followed by a string, (n-char-sequence), where n-char-sequence specifies in an implementation-dependent way the type of NAN (see NOTES).

RETURN VALUE

These functions return the converted value, if any.

If `endptr` is not NULL, a pointer to the character after the last character used in the conversion is stored in the location referenced by `endptr`.

If no conversion is performed, zero is returned and (unless `endptr` is null) the value of `nptr` is stored in the location referenced by `endptr`.

If the correct value would cause overflow, plus or minus `HUGE_VAL`, `HUGE_VALF`, or `HUGE_VALL` is returned (according to the return type and sign of the value), and `ERANGE` is stored in `errno`.

If the correct value would cause underflow, a value with magnitude no larger than `DBL_MIN`, `FLT_MIN`, or `LDBL_MIN` is returned and `ERANGE` is stored in `errno`.

ERRORS

`ERANGE` Overflow or underflow occurred.

ATTRIBUTES

For an explanation of the terms used in this section, see [attributes\(7\)](#).

??

?Interface ? Attribute ? Value ?

??

?`strtod()`, `strtof()`, `strtold()` ? Thread safety ? MT-Safe locale ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

`strtod()` was also described in C89.

NOTES

Since 0 can legitimately be returned on both success and failure, the calling program should set `errno` to 0 before the call, and then determine if an error occurred by checking whether `errno` has a nonzero value after the call.

In the glibc implementation, the `n-char-sequence` that optionally follows "NAN" is interpreted as an integer number (with an optional '0' or '0x' prefix to select base 8 or 16) that is to be placed in the mantissa component of the returned value.

EXAMPLES

See the example on the `strtol(3)` manual page; the use of the functions described in this manual page is similar.

SEE ALSO

`atof(3)`, `atoi(3)`, `atol(3)`, `nan(3)`, `nanf(3)`, `nanl(3)`, `strfromd(3)`, `strtol(3)`, `strtoul(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.