



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd-hibernate-resume-generator.8'

\$ man systemd-hibernate-resume-generator.8

SYSTEMD-HIBERNATE-RESUME-GENERATOR(8)

NAME

systemd-hibernate-resume-generator - Unit generator for resume= kernel parameter

SYNOPSIS

/lib/systemd/system-generators/systemd-hibernate-resume-generator

DESCRIPTION

systemd-hibernate-resume-generator is a generator that initiates the procedure to resume the system from hibernation. It instantiates the systemd-hibernate-resume@.service(8) unit according to the value of resume= parameter specified on the kernel command line, which will instruct the kernel to resume the system from the hibernation image on that device.

KERNEL COMMAND LINE

systemd-hibernate-resume-generator understands the following kernel command line

parameters:

resume=

Takes a path to the resume device. Both persistent block device paths like /dev/disk/by-foo/bar and fstab(5)-style specifiers like "FOO=bar" are supported.

resumeoptions=

Takes the resume device mount options to use. Defaults rootflags= if not specified.

noresume

Do not try to resume from hibernation. If this parameter is present, resume= is ignored.

SEE ALSO

systemd(1), systemd-hibernate-resume@.service(8), kernel-command-line(7)

systemd 249

SYSTEMD-HIBERNATE-RESUME-GENERATOR(8)