Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd-sysv-generator.8'

$ man systemd-sysv-generator.8

SYSTEMD-SYSV-GENERATOR(8)   systemd-sysv-generator   SYSTEMD-SYSV-GENERATOR(8)

NAME

    systemd-sysv-generator - Unit generator for SysV init scripts

SYNOPSIS

    /lib/systemd/system-generators/systemd-sysv-generator

DESCRIPTION

    systemd-sysv-generator is a generator that creates wrapper .service units for SysV init[1]

    scripts in /etc/init.d/* at boot and when configuration of the system manager is reloaded.

    This will allow systemd(1) to support them similarly to native units.

    LSB headers[2] in SysV init scripts are interpreted, and the ordering specified in the

    header is turned into dependencies between the generated unit and other units. The LSB

    facilities "$remote_fs", "$network", "$named", "$portmap", "$time" are supported and will

    be turned into dependencies on specific native systemd targets. See systemd.special(7) for

    more details.

    SysV runlevels have corresponding systemd targets (runlevelX.target). The wrapper unit

    that is generated will be wanted by those targets which correspond to runlevels for which

    the script is enabled.

    systemd does not support SysV scripts as part of early boot, so all wrapper units are

    ordered after basic.target.

    systemd-sysv-generator implements systemd.generator(7).

SEE ALSO

    systemd(1), systemd.service(5), systemd.target(5)

NOTES

1. SysV init

   https://savannah.nongnu.org/projects/sysvinit

2. LSB headers

   http://refspecs.linuxbase.org/LSB_3.1.1/LSB-Core-generic/LSB-Core-generic/iniscrptact.html