



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'systemd-timedated.8'***

***\$ man systemd-timedated.8***

SYSTEMD-TIMEDATED.SERVICE(8)    systemd-timedated.service    SYSTEMD-TIMEDATED.SERVICE(8)

NAME

systemd-timedated.service, systemd-timedated - Time and date bus mechanism

SYNOPSIS

systemd-timedated.service

/lib/systemd/systemd-timedated

DESCRIPTION

systemd-timedated.service is a system service that may be used as a mechanism to change the system clock and timezone, as well as to enable/disable network time synchronization.

systemd-timedated is automatically activated on request and terminates itself when it is unused.

The tool `timedatectl(1)` is a command line client to this service.

systemd-timedated currently offers access to the following four settings:

- ? The system time
- ? The system timezone
- ? A boolean controlling whether the system RTC is in local or UTC timezone
- ? Whether the time synchronization service is enabled/started or disabled/stopped, see next section.

See `org.freedesktop.timedate1(5)` and `org.freedesktop.LogControl1(5)` for information about the D-Bus API.

LIST OF NETWORK TIME SYNCHRONIZATION SERVICES

systemd-timesyncd will look for files with a ".list" extension in `ntp-units.d/`

directories. Each file is parsed as a list of unit names, one per line. Empty lines and

lines with comments ("#") are ignored. Files are read from /usr/lib/systemd/ntp-units.d/ and the corresponding directories under /etc/, /run/, /usr/local/lib/. Files in /etc/ override files with the same name in /run/, /usr/local/lib/, and /lib/. Files in /run/ override files with the same name under /usr/. Packages should install their configuration files in /usr/lib/ (distribution packages) or /usr/local/lib/ (local installs).

Example 1. ntp-units.d/ entry for systemd-timesyncd

```
# /usr/lib/systemd/ntp-units.d/80-systemd-timesync.list
systemd-timesyncd.service
```

If the environment variable \$SYSTEMD\_TIMEDATED\_NTP\_SERVICES is set, systemd-timesyncd will parse the contents of that variable as a colon-separated list of unit names. When set, this variable overrides the file-based list described above.

Example 2. An override that specifies that chronyd should be used if available

```
SYSTEMD_TIMEDATED_NTP_SERVICES=chronyd.service:systemd-timesyncd.service
```

#### SEE ALSO

systemd(1), timedatectl(1), localtime(5), hwclock(8), systemd-timesyncd(8)

systemd 249

SYSTEMD-TIMEDATED.SERVICE(8)