Full credit is given to the above companies including the OS that this PDF file was generated!

Linux Ubuntu 22.4.5 Manual Pages on command 't1ascii.1'

$ man t1ascii.1

T1ASCII(1)   General Commands Manual   T1ASCII(1)

NAME

    t1ascii - convert PostScript Type 1 font from binary to ASCII

SYNOPSIS

    t1ascii [-l length] [input [output]]

DESCRIPTION

    t1ascii converts Adobe Type 1 font programs in PFB (binary) format to PFA (hexadec?

    imal) format. If the file output is not specified output goes to the standard out?

    put. If the file input is not specified input comes from the standard input.

OPTIONS

    --line-length=num, -l num

        Set the maximum length of encrypted lines in the output to num. (These are

        the lines consisting wholly of hexadecimal digits.) The default is 64.

    --warnings, -w

        Warn when the input font contains lines longer than 255 characters.   Long

        lines don't strictly conform to Adobe's Document Structuring Conventions, and

        may cause problems with older software.

SEE ALSO

    t1binary(1), t1unmac(1), t1mac(1), t1asm(1), t1disasm(1)

    Adobe Type 1 Font Format

AUTHORS

    Lee Hetherington (ilh@lcs.mit.edu)

Eddie Kohler (ekohler@gmail.com)

Ported to Microsoft C/C++ Compiler and MS-DOS operating system by Kai-Uwe Herbing

(herbing@netmbx.netmbx.de).

Version 1.41   T1ASCII(1)