



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'tcgetpgrp.3'

\$ man tcgetpgrp.3

TCGETPGRP(3) Linux Programmer's Manual TCGETPGRP(3)

NAME

tcgetpgrp, tcsetpgrp - get and set terminal foreground process group

SYNOPSIS

```
#include <unistd.h>

pid_t tcgetpgrp(int fd);

int tcsetpgrp(int fd, pid_t pgrp);
```

DESCRIPTION

The function `tcgetpgrp()` returns the process group ID of the foreground process group on the terminal associated to `fd`, which must be the controlling terminal of the calling process.

The function `tcsetpgrp()` makes the process group with process group ID `pgrp` the foreground process group on the terminal associated to `fd`, which must be the controlling terminal of the calling process, and still be associated with its session. Moreover, `pgrp` must be a (nonempty) process group belonging to the same session as the calling process.

If `tcsetpgrp()` is called by a member of a background process group in its session, and the calling process is not blocking or ignoring `SIGTTOU`, a `SIGTTOU` signal is sent to all members of this background process group.

RETURN VALUE

When `fd` refers to the controlling terminal of the calling process, the function `tcgetpgrp()` will return the foreground process group ID of that terminal if there is one, and some value larger than 1 that is not presently a process group ID otherwise. When `fd` does not refer to the controlling terminal of the calling process, -1 is returned, and `errno` is

set appropriately.

When successful, tcsetpgrp() returns 0. Otherwise, it returns -1, and errno is set appropriately.

ERRORS

EBADF fd is not a valid file descriptor.

EINVAL pgrp has an unsupported value.

ENOTTY The calling process does not have a controlling terminal, or it has one but it is not described by fd, or, for tcsetpgrp(), this controlling terminal is no longer associated with the session of the calling process.

EPERM pgrp has a supported value, but is not the process group ID of a process in the same session as the calling process.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?tcgetpgrp(), tcsetpgrp() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

NOTES

These functions are implemented via the TIOCGPRG and TIOCSPGRP ioctls.

History

The ioctls appeared in 4.2BSD. The functions are POSIX inventions.

SEE ALSO

setpgid(2), setsid(2), credentials(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.