



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'tipc-media.8'

\$ man tipc-media.8

TIPC-MEDIA(8) Linux TIPC-MEDIA(8)

NAME

tipc-media - list or modify media properties

SYNOPSIS

tipc media set { priority PRIORITY | tolerance TOLERANCE | window WINDOW } media MEDIA

tipc media get { priority | tolerance | window } media MEDIA

tipc media list

OPTIONS

Options (flags) that can be passed anywhere in the command chain.

-h, --help

Show help about last valid command. For example tipc media --help will show media help and tipc --help will show general help. The position of the option in the string is irrelevant.

DESCRIPTION

Media properties

priority

Default link priority inherited by all bearers subsequently enabled on a media. For more info about link priority see tipc-link(8)

tolerance

Default link tolerance inherited by all bearers subsequently enabled on a media. For more info about link tolerance see tipc-link(8)

window

Default link window inherited by all bearers subsequently enabled on a media. For

more info about link window see `tipc-link(8)`

EXIT STATUS

Exit status is 0 if command was successful or a positive integer upon failure.

SEE ALSO

`tipc(8)`, `tipc-bearer(8)`, `tipc-link(8)`, `tipc-nametable(8)`, `tipc-node(8)`, `tipc-peer(8)`,
`tipc-socket(8)`

REPORTING BUGS

Report any bugs to the Network Developers mailing list [<netdev@vger.kernel.org>](mailto:netdev@vger.kernel.org) where the development and maintenance is primarily done. You do not have to be subscribed to the list to send a message there.

AUTHOR

Richard Alpe [<richard.alpe@ericsson.com>](mailto:richard.alpe@ericsson.com)

`iproute2`

02 Jun 2015

`TIPC-MEDIA(8)`