



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'tracker3-info.1'

\$ man tracker3-info.1

TRACKER3-INFO(1) Tracker manual TRACKER3-INFO(1)

NAME

tracker3-info - Retrieve all information available for a certain file.

SYNOPSIS

tracker3 info [options...] <file1> [[file2] ...]

DESCRIPTION

tracker3 info asks for all the known metadata available for the given file.

Multiple file arguments can be provided to retrieve information about multiple files.

The file argument can be either a local path or a URI. It also does not have to be an absolute path.

OPTIONS

-f, --full-namespaces

By default, all keys and values reported about any given file are returned in shortened form, for example, nie:title is shown instead of <http://tracker.api.gnome.org/ontology/v3/nie#title>. This makes things much easier to see generally and the output is less cluttered. This option reverses that so FULL namespaces are shown instead.

-c, --plain-text-content

If the resource being displayed has nie:PlainTextContent (i.e. information about the content of the resource, which could be the contents of a file on the disk), then this option displays that in the output.

-i, --resource-is-iri

In most cases, the file argument supplied points to a URL or PATH which is queried for

according to the resource associated with it by `nie:url`. However, in cases where the file specified turns out to be the actual URN itself, this argument is required to tell "tracker3 info" not to do the extra step of looking up the URN related by `nie:url`.

For example, consider that you store URNs by the actual URL itself and use the unique `nie:url` in another resource (which is quite reasonable when using containers and multi-resource conditions), you would need this argument to tell "tracker3 info" that the file supplied is actually a URN not URL.

`-t, --turtle`

Output results as Turtle RDF. If `-f` is enabled, full URIs are shown for subjects, predicates and objects; otherwise, shortened URIs are used, and all the prefixes Tracker knows about are printed at the top of the output.

SEE ALSO

`tracker3-sparql(1)`.

<http://nepomuk.semanticdesktop.org/> <http://www.w3.org/TR/rdf-sparql-query/>

3.3.3

12/01/2023

TRACKER3-INFO(1)