Rocky Enterprise Linux 9.2 Manual Pages on command 'tzselect.8'

$ man tzselect.8

TZSELECT(8)   Linux System Administration   TZSELECT(8)

NAME

   tzselect - select a timezone

SYNOPSIS

   tzselect

DESCRIPTION

   The tzselect program asks the user for information about the current location, and outputs

   the resulting timezone description to standard output. The output is suitable as a value

   for the TZ environment variable.

   All interaction with the user is done via standard input and standard error.

EXIT STATUS

   The exit status is zero if a timezone was successfully obtained from the user, and is non?

   zero otherwise.

ENVIRONMENT

   AWK   Name of a POSIX-compliant awk program (default: awk).

   TZDIR Name of the directory containing timezone data files (default: /usr/share/zone?

      info).

FILES

   TZDIR/iso3166.tab

      Table of ISO 3166 2-letter country codes and country names.

   TZDIR/zone.tab

      Table of country codes, latitude and longitude, TZ values, and descriptive com?

      ments.

TZDIR/TZ

Timezone data file for timezone TZ.

SEE ALSO

tzfile(5), zdump(8), zic(8)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the

project, information about reporting bugs, and the latest version of this page, can be

found at https://www.kernel.org/doc/man-pages/.

<div align="center">2007-05-18   TZSELECT(8)</div>