



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'unimplemented.2'

\$ man unimplemented.2

UNIMPLEMENTED(2) Linux Programmer's Manual UNIMPLEMENTED(2)

NAME

afs_syscall, break, fattach, fdetach, ftime, getmsg, getpmsg, gtty, isastream, lock, mad?
vise1, mpx, prof, profil, putmsg, putpmsg, security, stty, tuxcall, ulimit, vserver -
unimplemented system calls

SYNOPSIS

Unimplemented system calls.

DESCRIPTION

These system calls are not implemented in the Linux kernel.

RETURN VALUE

These system calls always return -1 and set errno to ENOSYS.

NOTES

Note that ftime(3), profil(3), and ulimit(3) are implemented as library functions.

Some system calls, like alloc_hugepages(2), free_hugepages(2), ioperm(2), iopl(2), and vm86(2) exist only on certain architectures.

Some system calls, like ipc(2), create_module(2), init_module(2), and delete_module(2) exist only when the Linux kernel was built with support for them.

SEE ALSO

syscalls(2)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

