



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'update-locale.8'

\$ man update-locale.8

UPDATE-LOCALE(8) System Manager's Manual UPDATE-LOCALE(8)

NAME

update-locale - Modify global locale settings

SYNTAX

update-locale [OPTIONS] [var=locale | var] [...]

DESCRIPTION

This program can be called by maintainer scripts when Debian packages are installed or removed, it updates the /etc/default/locale file to reflect changes in system configuration related to global locale settings. When variables have no value assigned, they are removed from the locale file. Some basic checks are performed to ensure that requested settings are valid.

OPTIONS

--help Display an help message and exit.

--reset

Variables which are not set on command-line are cleared out.

--locale-file FILE

Define file containing locale variables. (Default: /etc/default/locale)

--no-checks

Do not perform sanity checks on locale variables.

EXAMPLE

The command

```
update-locale LANG=en_CA.UTF-8 LANGUAGE
```

sets LANG to en_CA.UTF-8 and removes definitions for LANGUAGE.

FILES

`/etc/default/locale`

File where global locale settings are stored.

AUTHOR

Denis Barbier <barbier@linuxfr.org>

SEE ALSO

`locale-gen(8)`, `locale(1)`

Debian GNU/Linux

April 2006

UPDATE-LOCALE(8)