Rocky Enterprise Linux 9.2 Manual Pages on command 'uuidparse.1'

$ man uuidparse.1

UUIDPARSE(1)   User Commands   UUIDPARSE(1)

NAME

    uuidparse - a utility to parse unique identifiers

SYNOPSIS

    uuidparse [options] uuid

DESCRIPTION

    This command will parse unique identifier inputs from either command line arguments or

    standard input. The inputs are white-space separated.

OUTPUT

  Variants

    ???

    ?   ?   ?

    ?NCS   ? Network Computing System   ?

    ?   ? identifier. These were the   ?

    ?   ? original UUIDs.   ?

    ???

    ?   ?   ?

    ?DCE   ? The Open Software Foundation?s   ?

    ?   ? (OSF) Distributed Computing   ?

    ?   ? Environment UUIDs.   ?

    ???

    ?   ?   ?

    ?Microsoft ? Microsoft Windows platform   ?

globally unique identifier (GUID).

other	Unknown variant. Usually invalid input data.

Types

nil	Special type for zero in type file.
time-based	The DCE time based.
DCE	The DCE time and MAC Address.
name-based	RFC 4122 md5sum hash.
random	RFC 4122 random.
sha1-based	RFC 4122 sha-1 hash.
unknown	Unknown type. Usually invalid input data.

OPTIONS

-J, --json

> Use JSON output format.

-n, --noheadings

> Do not print a header line.

-o, --output

> Specify which output columns to print. Use --help to get a list of all supported
>
> columns.

-r, --raw

> Use the raw output format.

-V, --version

> Display version information and exit.

-h, --help

> Display help text and exit.

AUTHORS

Sami Kerola <kerolasa@iki.fi>

SEE ALSO

uuidgen(1), libuuid(3), RFC 4122 <https://tools.ietf.org/html/rfc4122>

REPORTING BUGS

For bug reports, use the issue tracker at https://github.com/karelzak/util-linux/issues.

AVAILABILITY

The uuidparse command is part of the util-linux package which can be downloaded from Linux

Kernel Archive <https://www.kernel.org/pub/linux/utils/util-linux/>.

util-linux 2.37.2   2021-06-02   UUIDPARSE(1)