



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'validlocale.8'

\$ man validlocale.8

validlocale(8)

validlocale(8)

NAME

validlocale - Test if a given locale is available

SYNTAX

validlocale <locale>

DESCRIPTION

Test if the locale given as argument is a valid locale. If it isn't, print on stdout the string to add to /etc/locale.gen to make locale-gen generate the locale (if it exists at all).

FILES

/usr/sbin/validlocale

/usr/share/i18n/SUPPORTED

ENVIRONMENT VARIABLES

DEFAULTCHARSET

Which charset to assume if the given locale is missing from the list of supported locales.

EXAMPLES

If you give a valid locale as parameter, it outputs a string specifying this on stderr:

```
% validlocale C  
locale 'C' valid and available
```

When given a invalid (not generated or just nonexistent), it outputs a string on stderr telling that this is an invalid locale, and a string to stdout with the string to add to /etc/locale.gen to have this locale generated:

```
% validlocale de_AU@euro  
locale 'de_AU@euro' not available  
de_AU@euro ISO-8859-15
```

AUTHORS

Petter Reinholdtsen <pere@hungry.com>

SEE ALSO

locale-gen(8), localedef(1), locale(1)

Petter Reinholdtsen 0.1 validlocale(8)