



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'vdpa-dev.8'

\$ man vdpa-dev.8

DEVLINK-DEV(8) Linux DEVLINK-DEV(8)

NAME

vdpa-dev - vdpa device configuration

SYNOPSIS

vdpa dev [OPTIONS] { COMMAND| help }

OPTIONS := { -V[ersion] }

vdpa dev show [DEV]

vdpa dev help

vdpa dev add name NAME mgmtdev MGMTDEV

vdpa dev del DEV

DESCRIPTION

vdpa dev show - display vdpa device attributes

DEV - specifies the vdpa device to show. If this argument is omitted all devices are listed.

Format is:

VDPA_DEVICE_NAME

vdpa dev add - add a new vdpa device.

name NAME

Name of the new vdpa device to add.

mgmtdev MGMTDEV

Name of the management device to use for device addition.

vdpa dev del - Delete the vdpa device.

DEV - specifies the vdpa device to delete.

EXAMPLES

```
vdpa dev show
```

Shows the all vdma devices on the system.

```
vdpa dev show foo
```

Shows the specified vdma device.

```
vdpa dev add name foo mgmtdev vdma_sim_net
```

Add the vdma device named foo on the management device vdma_sim_net.

```
vdpa dev del foo
```

Delete the vdma device named foo which was previously created.

SEE ALSO

vdma(8), vdma-mgmtdev(8),

AUTHOR

Parav Pandit <parav@nvidia.com>

iproute2

5 Jan 2021

DEVLINK-DEV(8)