



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'wcscmp.3'

\$ man wcscmp.3

WCSCMP(3) Linux Programmer's Manual WCSCMP(3)

NAME

wcscmp - compare two wide-character strings

SYNOPSIS

```
#include <wchar.h>

int wcscmp(const wchar_t *s1, const wchar_t *s2);
```

DESCRIPTION

The wcscmp() function is the wide-character equivalent of the strcmp(3) function. It compares the wide-character string pointed to by s1 and the wide-character string pointed to by s2.

RETURN VALUE

The wcscmp() function returns zero if the wide-character strings at s1 and s2 are equal. It returns an integer greater than zero if at the first differing position i, the corresponding wide-character s1[i] is greater than s2[i]. It returns an integer less than zero if at the first differing position i, the corresponding wide-character s1[i] is less than s2[i].

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?wcscmp() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

`strcmp(3)`, `wscasecmp(3)`, `wmemcmp(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

WCSCMP(3)