



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'wmemset.3'

\$ man wmemset.3

WMEMSET(3) Linux Programmer's Manual WMEMSET(3)

NAME

wmemset - fill an array of wide-characters with a constant wide character

SYNOPSIS

```
#include <wchar.h>

wchar_t *wmemset(wchar_t *wcs, wchar_t wc, size_t n);
```

DESCRIPTION

The wmemset() function is the wide-character equivalent of the memset(3) function. It fills the array of n wide-characters starting at wcs with n copies of the wide character wc.

RETURN VALUE

wmemset() returns wcs.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??
?Interface ? Attribute ? Value ?
??
?wmemset() ? Thread safety ? MT-Safe ?
??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

SEE ALSO

memset(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

WMEMSET(3)