



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'zenity.1'***

**\$ man zenity.1**

ZENITY(1) General Commands Manual ZENITY(1)

#### NAME

zenity - display GTK+ dialogs

#### SYNOPSIS

zenity [options]

#### DESCRIPTION

zenity is a program that will display GTK+ dialogs, and return (either in the return code, or on standard output) the users input. This allows you to present information, and ask for information from the user, from all manner of shell scripts.

For example, zenity --question will return either 0, 1 or 5, depending on whether the user pressed OK, Cancel or timeout has been reached. zenity --entry will output on standard output what the user typed into the text entry field.

Comprehensive documentation is available in the GNOME Help Browser.

#### OPTIONS

This program follows the usual GNU command line syntax, with long options starting with two dashes ('-').

Dialog options

--calendar

Display calendar dialog

--entry

Display text entry dialog

--error

Display error dialog

--file-selection  
Display file selection dialog

--info Display info dialog

--list Display list dialog

--notification  
Display notification

--progress  
Display progress indication dialog

--question  
Display question dialog

--text-info  
Display text information dialog

--warning  
Display warning dialog

--scale  
Display scale dialog

--color-selection  
Display color selection dialog

--password  
Display password dialog

--forms  
Display forms dialog

General options

--title=TITLE  
Set the dialog title

--window-icon=ICONPATH  
Set the window icon with the path to an image. Alternatively, one of the four stock icons can be used: 'error', 'info', 'question' or 'warning'

--icon-name=ICONNAME  
The name of the icon to display on the dialog to override the default stock icons

--width=WIDTH  
Set the dialog width

--height=HEIGHT

Set the dialog height

--timeout=TIMEOUT

Set the dialog timeout in seconds

Calendar options

--text=STRING

Set the dialog text

--day=INT

Set the calendar day

--month=INT

Set the calendar month

--year=INT

Set the calendar year

--date-format=PATTERN

Set the format for the returned date. The default depends on the user locale or be set with the strftime style. For example %A %d/%m/%y

Text entry options

--text=STRING

Set the dialog text

--entry-text=STRING

Set the entry text

--hide-text

Hide the entry text

Error options

--text=STRING

Set the dialog text

--no-wrap

Do not enable text wrapping

--no-markup

Do not enable pango markup

File selection options

--filename=FILENAME

Set the file or directory to be selected by default

--multiple

Allow selection of multiple filenames in file selection dialog

--directory  
Activate directory-only selection

--save Activate save mode

--separator=SEPARATOR  
Specify separator character when returning multiple filenames

--confirm-overwrite  
Confirm file selection if filename already exists

--file-filter=NAME | PATTERN1 PATTERN2  
Sets a filename filter

Info options

--text=STRING  
Set the dialog text

--no-wrap  
Do not enable text wrapping

--no-markup  
Do not enable pango markup

List options

--text=STRING  
Set the dialog text

--column=STRING  
Set the column header

--checklist  
Use check boxes for first column

--radiolist  
Use radio buttons for first column

--separator=STRING  
Set output separator character

--multiple  
Allow multiple rows to be selected

--editable  
Allow changes to text

--print-column=NUMBER

Specify what column to print to standard output. The default is to return the first column. 'ALL' may be used to print all columns.

--hide-column=NUMBER

Hide a specific column

--hide-header

Hides the column headers

Notification options

--text=STRING

Set the notification text

--listen

Listen for commands on stdin. Commands include 'message', 'tooltip', 'icon', and 'visible' separated by a colon. For example, 'message: Hello world', 'visible: false', or 'icon: /path/to/icon'. The icon command also accepts the four stock icon: 'error', 'info', 'question', and 'warning'

Progress options

--text=STRING

Set the dialog text

--percentage=INT

Set initial percentage

--auto-close

Close dialog when 100% has been reached

--auto-kill

Kill parent process if cancel button is pressed

--pulsate

Pulsate progress bar

--no-cancel

Hides the cancel button

Question options

--text=STRING

Set the dialog text

--no-wrap

Do not enable text wrapping

--no-markup

Do not enable pango markup

--ok-label

Set the text of the OK button

--cancel-label

Set the text of the cancel button

Text options

--filename=FILENAME

Open file

--editable

Allow changes to text

--checkbox=TEXT

Enable a checkbox for use like a 'I read and accept the terms.'

--ok-label

Set the text of the OK button

--cancel-label

Set the text of the cancel button

Warning options

--text=STRING

Set the dialog text

--no-wrap

Do not enable text wrapping

--no-markup

Do not enable pango markup

Scale options

--text=STRING

Set the dialog text

--value=VALUE

Set initial value

--min-value=VALUE

Set minimum value

--max-value=VALUE

Set maximum value

--step=VALUE

Set step size

--print-partial

Print partial values

--hide-value

Hide value

Color selection options

--color=VALUE

Set the initial color

--show-palette

Show the palette

Password dialog options

--username

Display the username field

Forms dialog options

--add-entry=FIELDNAME

Add a new Entry in forms dialog

--add-password=FIELDNAME

Add a new Password Entry in forms dialog

--add-calendar=FIELDNAME

Add a new Calendar in forms dialog

--text=STRING

Set the dialog text

--separator=STRING

Set output separator character

--forms-date-format=PATTERN

Set the format for the returned date. The default depends on the user locale or be set with the strftime style. For example %A %d/%m/%y

Miscellaneous options

-?, --help

Show summary of options.

--about

Display an about dialog.

--version

Show version of program.

Also the standard GTK+ options are accepted. For more information about the GTK+ options, execute following command.

```
zenity --help-gtk
```

## ENVIRONMENT

Normally, zenity detects the terminal window from which it was launched and keeps itself above that window. This behavior can be disabled by unsetting the WINDOWID environment variable.

## EXAMPLES

Display a file selector with the title Select a file to remove. The file selected is returned on standard output.

```
zenity --title="Select a file to remove" --file-selection
```

Display a text entry dialog with the title Select Host and the text Select the host you would like to flood-ping. The entered text is returned on standard output.

```
zenity --title "Select Host" --entry --text "Select the host you would like to  
flood-ping"
```

Display a dialog, asking Microsoft Windows has been found! Would you like to remove it?. The return code will be 0 (true in shell) if OK is selected, and 1 (false) if Cancel is selected.

```
zenity --question --title "Alert" --text "Microsoft Windows has been found! Would  
you like to remove it?"
```

Show the search results in a list dialog with the title Search Results and the text Find? ing all header files....

```
find . -name '*.\h' | zenity --list --title "Search Results" --text "Finding all  
header files.." --column "Files"
```

Show a notification in the message tray

```
zenity --notification --window-icon=update.png --text "System update necessary!"
```

Display a weekly shopping list in a check list dialog with Apples and Oranges pre selected

```
zenity --list --checklist --column "Buy" --column "Item" TRUE Apples TRUE Oranges  
FALSE Pears FALSE Toothpaste
```

Display a progress dialog while searching for all the postscript files in your home directory

```
find $HOME -name '*.ps' | zenity --progress --pulsate
```

## AUTHOR

Zenity was written by Glynn Foster <glynn.foster@sun.com>.

This manual page was written by Ross Burton <ross@burtonini.com>.

## SEE ALSO

[dialog\(1\)](#)

December 2011

[ZENITY\(1\)](#)