

Full credit is given to the above companies including the OS that this TDF file was generated!

PowerShell Get-Help on command 'Add-NetEventVmNetworkAdapter'

PS C:\Users\wahid> Get-Help Add-NetEventVmNetworkAdapter

NAME

Add-NetEventVmNetworkAdapter

SYNOPSIS

Adds a virtual network adapter as a filter on the provider.

SYNTAX

Add-NetEventVmNetworkAdapter [-Name] <String> [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-ThrottleLimit <Int32>] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Add-NetEventVmNetworkAdapter cmdlet adds a network adapter of a virtual machine as a filter on a Remote Packet Capture provider. Specify the name of the virtual network adapter. The protocol stack uses multiple layers to transmit, receive, and process network traffic as packets. The provider logs network traffic as Event Tracing for Windows (ETW) events.

Use this cmdlet multiple times to add multiple adapters. To see which virtual

adapters belong to the provider, use the Get-NetEventVmNetworkAdapter cmdlet.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession (https://go.microsoft.com/fwlink/p/?LinkId=227967) or [Get-CimSession](https://go.microsoft.com/fwlink/p/?LinkId=227966)cmdlet. The default is the current session on the local computer.

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

-Name <String>

Specifies a name for the virtual network adapter.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then Windows PowerShellr calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216).

--- Example 1: Add a virtual network adapter to the provider ---

PS C:\>New-NetEventSession -Name "NESession01" PS C:\> Add-NetEventPacketCaptureProvider -SessionName "NESession01" PS C:\> Add-NetEventVMNetworkAdapter -Name "LargeGuid"

This example adds a virtual network adapter as a filter on the Remote Packet Capture provider for a network session. After you complete these commands to configure the network session, you can start and stop the event and packet capture for the network session by using the Start-NetEventSession and Stop-NetEventSession cmdlets.

The first command uses the New-NetEventSession cmdlet to create a network session named NESession01.

The second command uses the Add-NetEventPacketCaptureProvider cmdlet to add a Remote Packet Capture provider for the session named NESession01.

The third command adds a virtual network adapter named LargeGuid as a filter on the Remote Packet Capture provider.

REMARKS

To see the examples, type: "get-help Add-NetEventVmNetworkAdapter -examples". For more information, type: "get-help Add-NetEventVmNetworkAdapter -detailed". For technical information, type: "get-help Add-NetEventVmNetworkAdapter -full". For online help, type: "get-help Add-NetEventVmNetworkAdapter -online"