



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Disable-BitLockerAutoUnlock'

PS C:\Users\wahid> Get-Help Disable-BitLockerAutoUnlock

NAME

Disable-BitLockerAutoUnlock

SYNOPSIS

Disables automatic unlocking for a BitLocker volume.

SYNTAX

Disable-BitLockerAutoUnlock [-MountPoint] <String[]> [-Confirm] [-WhatIf]
[<CommonParameters>]

DESCRIPTION

The Disable-BitLockerAutoUnlock cmdlet disables automatic unlocking for a volume protected by BitLocker Disk Encryption. The cmdlet removes automatic unlocking keys for specified volumes stored on a volume that hosts an operating system.

You can configure BitLocker to automatically unlock volumes that do not host an operating system. After a user unlocks the operating system volume, BitLocker uses encrypted information stored in the registry and volume

metadata to access data volumes that use automatic unlocking.

You can specify a volume by drive letter, or you can specify a BitLocker volume object. You must remove automatic unlocking keys before you can disable BitLocker by using the Disable-BitLocker cmdlet. You can use the Clear-BitLockerAutoUnlock cmdlet to remove keys for all the volumes configured to use automatic unlocking instead of just specified volumes.

For an overview of BitLocker, see BitLocker Drive Encryption Overview (<https://technet.microsoft.com/en-us/library/cc732774.aspx>) on TechNet.

PARAMETERS

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

-MountPoint <String[]>

Specifies an array of drive letters or BitLocker volume objects. The cmdlet disables automatic unlocking for the volumes specified. To obtain a BitLocker volume object, use the Get-BitLockerVolume cmdlet.

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters](https://go.microsoft.com/fwlink/?LinkID=113216) (<https://go.microsoft.com/fwlink/?LinkID=113216>).

----- Example 1: Disable automatic unlocking for a volume -----

```
PS C:\> Disable-BitLockerAutoUnlock -MountPoint "E:"
```

This command disables automatic unlocking for the specified BitLocker volume.

REMARKS

To see the examples, type: "get-help Disable-BitLockerAutoUnlock -examples".

For more information, type: "get-help Disable-BitLockerAutoUnlock -detailed".

For technical information, type: "get-help Disable-BitLockerAutoUnlock -full".

For online help, type: "get-help Disable-BitLockerAutoUnlock -online"