



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Disable-LocalUser'

PS C:\Users\wahid> Get-Help Disable-LocalUser

NAME

Disable-LocalUser

SYNOPSIS

Disables a local user account.

SYNTAX

Disable-LocalUser [-InputObject] <Microsoft.PowerShell.Commands.LocalUser[]>
[-Confirm] [-WhatIf] [<CommonParameters>]

Disable-LocalUser [-Name] <System.String[]> [-Confirm] [-WhatIf]
[<CommonParameters>]

Disable-LocalUser [-SID] <System.Security.Principal.SecurityIdentifier[]>
[-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The `Disable-LocalUser` cmdlet disables local user accounts. When a user account is disabled, the user cannot log on. When a user account is enabled,

the user can log on.

> [!NOTE] > The Microsoft.PowerShell.LocalAccounts module is not available in 32-bit PowerShell on a > 64-bit system.

PARAMETERS

-InputObject <Microsoft.PowerShell.Commands.LocalUser[]>

Specifies an array of user accounts that this cmdlet disables. To obtain a user account, use the `Get-LocalUser` cmdlet.

-Name <System.String[]>

Specifies an array of names of the user accounts that this cmdlet disables.

-SID <System.Security.Principal.SecurityIdentifier[]>

Specifies an array of user accounts that this cmdlet disables.

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

----- Example 1: Disable an account by specifying a name -----

```
Disable-LocalUser -Name "Admin02"
```

This command disables the user account named Admin02.

----- Example 2: Disable an account by using the pipeline -----

```
Get-LocalUser Guest | Disable-LocalUser
```

This command gets the built-in Guest account by using `Get-LocalUser``, and then passes it to the current cmdlet by using the pipeline operator(`|``). That cmdlet disables that account.

REMARKS

To see the examples, type: "get-help Disable-LocalUser -examples".

For more information, type: "get-help Disable-LocalUser -detailed".

For technical information, type: "get-help Disable-LocalUser -full".

For online help, type: "get-help Disable-LocalUser -online"