



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Disable-NetAdapterPowerManagement'

PS C:\Users\wahid> Get-Help Disable-NetAdapterPowerManagement

NAME

Disable-NetAdapterPowerManagement

SYNOPSIS

Disables specific power management features on a network adapter.

SYNTAX

```
Disable-NetAdapterPowerManagement [-Name] <String[]> [-ArpOffload] [-AsJob]
[-CimSession <CimSession[]>] [-Confirm] [-D0PacketCoalescing]
[-DeviceSleepOnDisconnect] [-IncludeHidden] [-NSOffload] [-NoRestart]
[-PassThru] [-RsnRekeyOffload] [-SelectiveSuspend] [-ThrottleLimit <Int32>]
[-WakeOnMagicPacket] [-WakeOnPattern] [-WhatIf] [<CommonParameters>]
```

```
Disable-NetAdapterPowerManagement [-ArpOffload] [-AsJob] [-CimSession
<CimSession[]>] [-Confirm] [-D0PacketCoalescing] [-DeviceSleepOnDisconnect]
[-IncludeHidden] -InterfaceDescription <String[]> [-NSOffload] [-NoRestart]
[-PassThru] [-RsnRekeyOffload] [-SelectiveSuspend] [-ThrottleLimit <Int32>]
[-WakeOnMagicPacket] [-WakeOnPattern] [-WhatIf] [<CommonParameters>]
```

```
Disable-NetAdapterPowerManagement [-ArpOffload] [-AsJob] [-CimSession
```

<CimSession[]> [-Confirm] [-D0PacketCoalescing] [-DeviceSleepOnDisconnect]
-InputObject <CimInstance[]> [-NSOffload] [-NoRestart] [-PassThru]
[-RsnRekeyOffload] [-SelectiveSuspend] [-ThrottleLimit <Int32>]
[-WakeOnMagicPacket] [-WakeOnPattern] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Disable-NetAdapterPowerManagement cmdlet disables specific power management features on a network adapter. If no power parameters are specified then all power management features are disabled.

PARAMETERS

-ArpOffload [<SwitchParameter>]

Indicates that the cmdlet manages the address resolution protocol (ARP) offload capability of the adapter.

The computer, when in low power mode using the ARP offload technology, is able to offload the responsibility of handling responses for incoming ARP protocol requests.

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete. The cmdlet immediately returns an object that represents the job and then displays the command prompt. You can continue to work in the session while the job completes. To manage the job, use the `*-Job` cmdlets. To get the job results, use the Receive-Job (<https://go.microsoft.com/fwlink/?LinkID=113372>)cmdlet. For more information about Windows PowerShell background jobs, see about_Jobs (<https://go.microsoft.com/fwlink/?LinkID=113251>).

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a

computer name or a session object, such as the output of a `New-CimSession` (<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or `[Get-CimSession](https://go.microsoft.com/fwlink/p/?LinkId=227966)` cmdlet. The default is the current session on the local computer.

`-Confirm [<SwitchParameter>]`

Prompts you for confirmation before running the cmdlet.

`-D0PacketCoalescing [<SwitchParameter>]`

Indicates that the cmdlet manages the D0 packet coalescing capability of the network adapter.

This feature enables power saving on the computer by reducing the number of receive interrupts. This reduces the number of receive interrupts by coalescing random broadcast or multicast packets. The processing overhead and power consumption is significantly reduced on the computer.

`-DeviceSleepOnDisconnect [<SwitchParameter>]`

Indicates that the cmdlet manages the device sleep on disconnect capability of the network adapter.

This feature allows the device to stand-by in a low power mode when media is disconnected and wake when media is connected again.

`-IncludeHidden [<SwitchParameter>]`

Indicates that the cmdlet includes both visible and hidden network adapters in the operation. By default only visible network adapters are included. If a wildcard character is used in identifying a network adapter and this parameter has been specified, then the wildcard string is matched against both hidden and visible network adapters.

`-InputObject <CimInstance[]>`

Specifies the input to this cmdlet. You can use this parameter, or you can

pipe the input to this cmdlet.

-InterfaceDescription <String[]>

Specifies an array of network adapter interface descriptions. For a physical network adapter this is typically the name of the vendor of the network adapter followed by a part number and description, such as `Contoso 12345 Gigabit Network Device`.

-NSOffload [<SwitchParameter>]

Indicates that the cmdlet manages the neighbor solicitation (NS) offload capability of the network adapter.

The computer, when in low power mode using the NS offload technology, is able to offload the handling of responses for incoming NS protocol requests.

-Name <String[]>

Specifies an array of network adapter names.

-NoRestart [<SwitchParameter>]

Indicates that the cmdlet does not restart the network adapter after completing the operation. Many advanced properties require restarting the network adapter before the new settings take effect.

-PassThru [<SwitchParameter>]

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

-RsnRekeyOffload [<SwitchParameter>]

Indicates that the cmdlet manages the Wi-Fi robust security network (RSN) rekey offload capability of the network adapter.

The computer, when it goes into sleep state, is able to offload the group

temporal key (GTK) rekeying for wake on wireless LAN (WoWLAN).

-SelectiveSuspend [<SwitchParameter>]

Indicates that the cmdlet manages the selective suspend capability of the network adapter.

The network drive interface specification (NDIS) selective suspend interface allows NDIS to suspend an idle network adapter by transitioning the adapter to a low-power state. This enables the computer to reduce the power overhead on the CPU and network adapter.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

-WakeOnMagicPacket [<SwitchParameter>]

Indicates that the cmdlet manages the wake on magic packet capability of the network adapter.

The magic packet is a broadcast frame containing anywhere within its payload 6 bytes of all 255 (FF FF FF FF FF FF) in hexadecimal), followed by sixteen repetitions of the 48-bit MAC address of the target computer, for a total of 102 bytes.

-WakeOnPattern [<SwitchParameter>]

Indicates that the cmdlet manages the wake on pattern capability of the network adapter.

A wake pattern refers to network packet filters that determine if incoming

network traffic should wake the computer. These patterns can be enabled on the network adapter.

The following wake patterns may be supported by a network adapter: - Wake Pattern

- Wake on new incoming TCP connection for IPv4 and IPv6 including TCP SYN IPv4 and TCP SYN IPv6.

- 802.1x re-authentication packets

- Bitmapped Patterns.

Most network adapters can be programmed with bit-mapped pattern filters. Bitmapped patterns are defined by a bit-map mask and a pattern filter. As a network packet is received, it is masked using the bitmap mask and then compared to the pattern filter. If there is a match, then the network adapter wakes the computer.

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

Example 1: Disable power management on a specified network adapter

```
PS C:\> Disable-NetAdapterPowerManagement -Name "Ethernet 1"
```

This command disables power management on the network adapter named Ethernet 1

and restarts the network adapter.

Example 2: Disable power management on a specified network adapter using InputObject

```
PS C:\> $NetAdapter1 = Get-NetAdapter -Name "Ethernet 3"
```

```
PS C:\> Disable-NetAdapterPowerManagement -InputObject $NetAdapter1
```

This first command gets the network adapter named Ethernet 3 and stores the result in the variable named \$NetAdapter1.

The second command disables the network adapter that is in the \$NetAdapter1 variable.

Example 3: Disable power management on the specified network adapter and do not restart it

```
PS C:\> Disable-NetAdapterPowerManagement -Name "Ethernet 4" -NoRestart
```

This command disables power management on the network adapter named Ethernet 4 and specifies that the network adapter is not restarted.

REMARKS

To see the examples, type: "get-help Disable-NetAdapterPowerManagement -examples".

For more information, type: "get-help Disable-NetAdapterPowerManagement -detailed".

For technical information, type: "get-help Disable-NetAdapterPowerManagement -full".

For online help, type: "get-help Disable-NetAdapterPowerManagement -online"