PowerShell Get-Help on command 'Disable-TlsCipherSuite'

PS C:\Users\wahid> Get-Help Disable-TlsCipherSuite

NAME

Disable-TlsCipherSuite

SYNOPSIS

Disables a TLS cipher suite.

SYNTAX

Disable-TlsCipherSuite [-Name] <System.String> [-Confirm] [-WhatIf]

[<CommonParameters>]

DESCRIPTION

The `Disable-TlsCipherSuite` cmdlet disables a cipher suite. This cmdlet

removes the cipher suite from the list of Transport Layer Security (TLS)

protocol cipher suites for the computer.

For more information about the TLS cipher suites, see the documentation for

the Enable-TlsCipherSuite cmdlet or type `Get-Help Enable-TlsCipherSuite`.

PARAMETERS

   -Name <System.String>

     Specifies the name of the TLS cipher suite to disable.

   -Confirm <System.Management.Automation.SwitchParameter>

     Prompts you for confirmation before running the cmdlet.

   -WhatIf <System.Management.Automation.SwitchParameter>

     Shows what would happen if the cmdlet runs. The cmdlet is not run.

   <CommonParameters>

     This cmdlet supports the common parameters: Verbose, Debug,

     ErrorAction, ErrorVariable, WarningAction, WarningVariable,

     OutBuffer, PipelineVariable, and OutVariable. For more information, see

     about_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216).

   -------------- Example 1: Disable a cipher suite --------------

   Disable-TlsCipherSuite -Name 'TLS_RSA_WITH_3DES_EDE_CBC_SHA'

   This command disables the cipher suite named TLS_RSA_WITH_3DES_EDE_CBC_SHA.

   The command removes the cipher suite from the list of TLS protocol cipher

   suites.

REMARKS

   To see the examples, type: "get-help Disable-TlsCipherSuite -examples".

   For more information, type: "get-help Disable-TlsCipherSuite -detailed".

   For technical information, type: "get-help Disable-TlsCipherSuite -full".

   For online help, type: "get-help Disable-TlsCipherSuite -online"