



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Disable-TlsSessionTicketKey'

PS C:\Users\wahid> Get-Help Disable-TlsSessionTicketKey

NAME

Disable-TlsSessionTicketKey

SYNOPSIS

Disables a TLS session ticket key.

SYNTAX

```
Disable-TlsSessionTicketKey [-ServiceAccountName]  
<System.Security.Principal.NTAccount> [-Confirm] [-WhatIf] [<CommonParameters>]
```

DESCRIPTION

The `Disable-TlsSessionTicketKey` cmdlet disables an administrator managed Transport Layer Security (TLS) session ticket key for the service account. The cmdlet disables the key for the TLS session by deleting the key and the corresponding rule that uses the key.

When you disable a TLS session ticket key for the service account, the service account cannot decrypt existing TLS session tickets. Disabling the TLS session ticket key can affect the performance of the TLS server. The TLS server cannot

create new session tickets and must negotiate session information between the client and the server every time the client connects to the TLS server.

TLS creates a session ticket by using the TLS Session Resumption without Server-Side State mechanism. For more information, see

`New-TlsSessionTicketKey` or type `Get-Help New-TlsSessionTicketKey`.

PARAMETERS

`-ServiceAccountName <System.Security.Principal.NTAccount>`

Specifies the name of a service account. The cmdlet disables the TLS session ticket key for the service account. Only System, LocalService, NetworkService, and SID of virtual accounts are supported.

`-Confirm <System.Management.Automation.SwitchParameter>`

Prompts you for confirmation before running the cmdlet.

`-WhatIf <System.Management.Automation.SwitchParameter>`

Shows what would happen if the cmdlet runs. The cmdlet is not run.

`<CommonParameters>`

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

----- Example 1: Disable a TLS session ticket key -----

```
Disable-TlsSessionTicketKey -ServiceAccountName NetworkService
```

This command disables the TLS session ticket key for the service account named NetworkService.

REMARKS

To see the examples, type: "get-help Disable-TlsSessionTicketKey -examples".

For more information, type: "get-help Disable-TlsSessionTicketKey -detailed".

For technical information, type: "get-help Disable-TlsSessionTicketKey -full".

For online help, type: "get-help Disable-TlsSessionTicketKey -online"