PowerShell Get-Help on command 'Enable-NetIPHttpsProfile'

PS C:\Users\wahid> Get-Help Enable-NetIPHttpsProfile

NAME

    Enable-NetIPHttpsProfile

SYNOPSIS

    Enables an IP-HTTPS configuration profile.

SYNTAX

    Enable-NetIPHttpsProfile [-AsJob] [-CimSession <CimSession[]>] [-Confirm]

    -Profile <String> [-ThrottleLimit <Int32>] [-WhatIf] [<CommonParameters>]

DESCRIPTION

    The Enable-NetIPHttpsProfile cmdlet enables an IP-HTTPS configuration profile.

    Only one configuration can be active at a time.

    An active configuration does not mean that IP-HTTPS is active. The active

    configuration may disable IP-HTTPS.

PARAMETERS

-AsJob [<SwitchParameter>]

   Runs the cmdlet as a background job. Use this parameter to run commands

   that take a long time to complete.

-CimSession <CimSession[]>

   Runs the cmdlet in a remote session or on a remote computer. Enter a

   computer name or a session object, such as the output of a New-CimSession

   (https://go.microsoft.com/fwlink/p/?LinkId=227967) or

   [Get-CimSession](https://go.microsoft.com/fwlink/p/?LinkId=227966)cmdlet.

   The default is the current session on the local computer.

-Confirm [<SwitchParameter>]

   Prompts you for confirmation before running the cmdlet.

-Profile <String>

   Specifies the name of the profile to enable.

-ThrottleLimit <Int32>

   Specifies the maximum number of concurrent operations that can be

   established to run the cmdlet. If this parameter is omitted or a value of

   `0` is entered, then Windows PowerShellr calculates an optimum throttle

   limit for the cmdlet based on the number of CIM cmdlets that are running

   on the computer. The throttle limit applies only to the current cmdlet,

   not to the session or to the computer.

-WhatIf [<SwitchParameter>]

   Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

   This cmdlet supports the common parameters: Verbose, Debug,

   ErrorAction, ErrorVariable, WarningAction, WarningVariable,

   OutBuffer, PipelineVariable, and OutVariable. For more information, see

   about_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216).

------- Example 1: Enable IP-HTTPS configuration profile -------

PS C:\>Enable-NetIPHttpsProfile -Profile "Redmond"

This command enables the IP-HTTPS configuration profile named Redmond.

REMARKS

To see the examples, type: "get-help Enable-NetIPHttpsProfile -examples".

For more information, type: "get-help Enable-NetIPHttpsProfile -detailed".

For technical information, type: "get-help Enable-NetIPHttpsProfile -full".

For online help, type: "get-help Enable-NetIPHttpsProfile -online"