



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Enable-ScheduledTask'

PS C:\Users\wahid> Get-Help Enable-ScheduledTask

NAME

Enable-ScheduledTask

SYNOPSIS

Enables a scheduled task.

SYNTAX

Enable-ScheduledTask [-InputObject] <CimInstance> [-AsJob] [-CimSession
<CimSession[]>] [-ThrottleLimit <Int32>] [<CommonParameters>]

Enable-ScheduledTask [-TaskName] <String> [[-TaskPath] <String>] [-AsJob]
[-CimSession <CimSession[]>] [-ThrottleLimit <Int32>] [<CommonParameters>]

DESCRIPTION

The Enable-ScheduledTask cmdlet enables a disabled scheduled task.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a `New-CimSession` (<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or `[Get-CimSession](https://go.microsoft.com/fwlink/p/?LinkId=227966)cmdlet`. The default is the current session on the local computer.

-InputObject <CimInstance>

Specifies the input object that is used in a pipeline command.

-TaskName <String>

Specifies the name of a scheduled task.

-TaskPath <String>

Specifies an array of one or more paths for scheduled tasks in Task Scheduler namespace. You can use "*" for a wildcard character query. You can use \ for the root folder. To specify a full TaskPath you need to include the leading and trailing \ *. If you do not specify a path, the cmdlet uses the root folder.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of 0 is entered, then Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

----- Example 1: Enable a scheduled task -----

```
PS C:\> Enable-ScheduledTask -TaskName "SystemScan"
```

TaskPath	TaskName	State
-----	-----	-----
\	SystemScan	Ready

This command enables the SystemScan task in the root folder.

----- Example 2: Enable all scheduled tasks in a folder -----

```
PS C:\> Get-ScheduledTask -TaskPath "\UpdateTasks\" | Enable-ScheduledTask
```

TaskPath	TaskName	State
-----	-----	-----
\UpdateTasks\	UpdateApps	Ready
\UpdateTasks\	UpdateDrivers	Ready

This command uses the Get-ScheduledTask cmdlet to get all scheduled tasks in the \UpdateTasks\ folder. It pipes this information to the Enable-ScheduledTasks cmdlet, which enables these scheduled tasks.

REMARKS

To see the examples, type: "get-help Enable-ScheduledTask -examples".

For more information, type: "get-help Enable-ScheduledTask -detailed".

For technical information, type: "get-help Enable-ScheduledTask -full".

For online help, type: "get-help Enable-ScheduledTask -online"