



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Get-NetAdapterStatistics'

PS C:\Users\wahid> Get-Help Get-NetAdapterStatistics

NAME

Get-NetAdapterStatistics

SYNOPSIS

Gets statistics from a network adapter.

SYNTAX

```
Get-NetAdapterStatistics [-AsJob] [-CimSession <CimSession[]>]
[-IncludeHidden] -InterfaceDescription <String[]> [-ThrottleLimit <Int32>]
[<CommonParameters>]
```

```
Get-NetAdapterStatistics [[-Name] <String[]>] [-AsJob] [-CimSession
<CimSession[]>] [-IncludeHidden] [-ThrottleLimit <Int32>] [<CommonParameters>]
```

DESCRIPTION

The Get-NetAdapterStatistics cmdlet gets networking statistics from a network adapter. The statistics include broadcast, multicast, discards, and errors.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete. The cmdlet immediately returns an object that represents the job and then displays the command prompt. You can continue to work in the session while the job completes. To manage the job, use the ``*-Job`` cmdlets. To get the job results, use the `Receive-Job` (<https://go.microsoft.com/fwlink/?LinkID=113372>) cmdlet. For more information about Windows PowerShell background jobs, see `about_Jobs` (<https://go.microsoft.com/fwlink/?LinkID=113251>).

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a `New-CimSession` (<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or `[Get-CimSession]` (<https://go.microsoft.com/fwlink/p/?LinkId=227966>) cmdlet. The default is the current session on the local computer.

-IncludeHidden [<SwitchParameter>]

Indicates that the cmdlet includes both visible and hidden network adapters in the operation. By default only visible network adapters are included. If a wildcard character is used in identifying a network adapter and this parameter has been specified, then the wildcard string is matched against both hidden and visible network adapters.

-InterfaceDescription <String[]>

Specifies an array of network adapter interface descriptions. For a physical network adapter this is typically the name of the vendor of the network adapter followed by a part number and description, such as ``Contoso 12345 Gigabit Network Device``.

-Name <String[]>

Specifies an array of network adapter names.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

Example 1: Display statistics for the specified network adapter

```
PS C:\> Get-NetAdapterStatistics -Name "MyAdapter"
```

This command displays statistics for the network adapter named MyAdapter.

Example 2: Display all statistics for the specified network adapter

```
PS C:\> Get-NetAdapterStatistics -Name "MyAdapter" | Format-List -Property "**"
```

This command displays all statistics for the network adapter named MyAdapter.

REMARKS

To see the examples, type: "get-help Get-NetAdapterStatistics -examples".

For more information, type: "get-help Get-NetAdapterStatistics -detailed".

For technical information, type: "get-help Get-NetAdapterStatistics -full".

For online help, type: "get-help Get-NetAdapterStatistics -online"