MyWebUniversity *







Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Get-Printer'

PS C:\Users\wahid> Get-Help Get-Printer

NAME

Get-Printer

SYNOPSIS

Retrieves a list of printers installed on a computer.

SYNTAX

Get-Printer [[-Name] <String[]>] [-AsJob] [-CimSession <CimSession[]>] [-ComputerName <String>] [-Full] [-ThrottleLimit <Int32>] [<CommonParameters>]

DESCRIPTION

The Get-Printer cmdlet retrieves a list of printers installed on a computer.

You can also use Get-Printer to retrieve the properties of a single printer, and then use that information as input into other cmdlets.

You can use wildcard characters with Get-Printer . You can use a Get-Printer in a Windows PowerShell remoting session.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession (https://go.microsoft.com/fwlink/p/?LinkId=227967) or

[Get-CimSession](https://go.microsoft.com/fwlink/p/?LinkId=227966)cmdlet.

The default is the current session on the local computer.

-ComputerName <String>

Specifies the name of the computer from which to retrieve the printer information.

-Full [<SwitchParameter>]

Specifies all the printer parameters to retrieve including RenderingMode and PermissionSDDL.

-Name <String[]>

Specifies the name of the printer about which to retrieve information.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then Windows PowerShellr calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,
ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see

about_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216).

----- Example 1: Get a list of printers -----

Get-Printer

This command retrieves a list of printers and printer connections on the local computer.

---- Example 2: Get the information for a specific printer ----

Get-Printer -Name "Microsoft XPS Document Writer"

This command retrieves information for one specific printer named Microsoft XPS Document Writer.

Example 3: Get the detailed information for a specific printer

Get-Printer -Name "Microsoft XPS Document Writer" | Format-List

This command retrieves detailed information for one specific printer named Microsoft XPS Document Writer.

---- Example 4: Get a list of printers on a remote computer ----

Get-Printer -ComputerName PrintServer

This command retrieves a list of printers from the computer named PrintServer.

Example 5: Get a list of printer objects and then rename the printers

\$Printer = Get-Printer -Name "Microsoft XPS Document Writer"

Rename-Printer -InputObject \$printer "MXDW"

The first command gets the printer named Microsoft XPS Document Writer, and then stores it in the \$Printer variable.

The second command renames the printer in \$Printer by using the Rename-Printer cmdlet.

REMARKS

To see the examples, type: "get-help Get-Printer -examples".

For more information, type: "get-help Get-Printer -detailed".

For technical information, type: "get-help Get-Printer -full".

For online help, type: "get-help Get-Printer -online"