PowerShell Get-Help on command 'Get-SecureBootPolicy'

PS C:\Users\wahid> Get-Help Get-SecureBootPolicy

NAME

    Get-SecureBootPolicy

SYNOPSIS

    Gets the publisher GUID and the policy version of the Secure Boot

    configuration policy.

SYNTAX

    Get-SecureBootPolicy [<CommonParameters>]

DESCRIPTION

    The Get-SecureBootPolicy cmdlet gets the publisher GUID and the policy version

    of the Secure Boot configuration policy.

    The cmdlet runs on both UEFI and BIOS (non-UEFI) computers.

    If the computer does not support Secure Boot or is a non-UEFI computer, this

    cmdlet displays the following:

`Secure Boot policy is not enabled on this machine.`

If you do not run Windows PowerShellr in administrator mode, this cmdlet
returns an error displaying the following:

`Incorrect authentication data.`

PARAMETERS

    <CommonParameters>

       This cmdlet supports the common parameters: Verbose, Debug,

       ErrorAction, ErrorVariable, WarningAction, WarningVariable,

       OutBuffer, PipelineVariable, and OutVariable. For more information, see

       about_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216).

    -------------- Example 1: Get Secure Boot policy --------------

    PS C:\> Get-SecureBootPolicy | Format-List

    Publisher: 77fa9abd-0359-4d32-bd60-28f4e78f784b

    Version : 1

    This command gets the publisher GUID and the policy version of the Secure Boot
    configuration policy.

REMARKS

    To see the examples, type: "get-help Get-SecureBootPolicy -examples".

    For more information, type: "get-help Get-SecureBootPolicy -detailed".

    For technical information, type: "get-help Get-SecureBootPolicy -full".

    For online help, type: "get-help Get-SecureBootPolicy -online"